

*Tenda*



All for better networking.

4G06c

N300 Wi-Fi 4G LTE Router

[www.tendacn.com](http://www.tendacn.com)

# Tenda



## 4G06c

### N300 Wi-Fi 4G LTE Router

Tenda 4G06c is an LTE Router that integrates LTE and high-speed Ethernet uplink access, providing users with flexible and diversified data access.



### Wiring-free Broadband access anywhere

With LTE signal coverage of the best performance and allowing you to receive Internet access without cable and fiber, it is the ideal choice for remote areas such as rural and suburban temporary stores, and holiday homes. Users can access the Internet anywhere and anytime.



### Share High-speed 4G Network

With advanced 4G LTE cellular network, the access rate is up to 150Mbps. Equipped with 2 high-gain 4G external antennas, you can access the Internet easily.



### Stronger and Wider Wi-Fi Signal

The high-gain 2.4GHz band enlarges your Wi-Fi coverage, still maintaining an outstanding Wi-Fi performance even after penetrating multiple walls.



### Share your Wi-Fi with up to 32 devices

The powerful 880MHz and 28nm processor makes it possible to share the Wi-Fi with up to 32 devices based on a dependable network.



### Instantly access a mobile network with a Mini SIM card

Access a mobile network instantly just with an authorized Mini SIM card.

Hardware Specification	
4G Catgory	LTE CAT.4
4G/3G standards	FDD LTE,TDD-LTE,WCDMA;
4G Mobile Bands	4G FDD LTE:B1/B2/B3/B4/B5/B7/B8/B20/B28AB; 4G TDD-LTE:Band38/Band40; 3G WCDMA:B1/B2/B5/B8 ; 2G GSM:B3/B8;
Max 4G+ speed	DL:150Mbps UL:50Mbps
Wi-Fi standards	802.11b/g/n
Wi-Fi frequency	2.4GHz
Wi-Fi speed	2.4GHz:300Mbps ;
Wi-Fi transmit Power	2.4GHz:up to 20dBm ;
Interface	1 × 10/100 Mbps LAN/WAN Port 1 × 10/100 Mbps LAN Port 1 × 2FF SIM Card Slot
Button	Power on/off WPS/Reset
Antennas	2 detachable 4G/3G Antennas; 2 Internal Wi-Fi Antennas;
LED indicators	Power Wi-Fi LAN Internet 4G/3G Signal strength(3 Bars)
Dimensions( L* W* H)	185*126*60mm
Weight	About 350g
Power supply	Power adapter : Input power AC 110V-220V 50/60Hz Output power : DC 9V==1A

### Software Specification

WAN Type	4G/3G/2G or Wired
4G/3G Features	Auto-APN Auto dial-up Roaming SMS(Send/Receive/Delete) USSD Data Limited PIN Management
Wi-Fi functions	Broadcast and Hide Wi-Fi name Guest network Wi-Fi schedule
Wi-Fi security	WEP,WPA-PSK, WPA2-PSK, WPA/WPA2
Software features	APP/Local/remote management Parental control DHCP(DHCP Server and Client) Virtual Server(UPnP/DMZ/Port Forwarding) DDNS(Dyn DNS, 88ip) VPN(PPTP Client/L2TP Client/PPTP Server) Firewall QOS Upgrade firmware from local or OTA IPV4/IPV6 TR069
Certifications	
	FCC Granted CE Granted ROHS Granted
Working Environment	
Temperature	Operating Temperature: 0°C~40°C Storage Temperature: -30°C~70°C
Humidity	Operating Humidity: 10% ~ 90% RH Non-condensing Storage Humidity: 5% ~ 90% RH Non-condensing
Package lists	
Contents	1 * 4G LTE Router 1 * Ethernet cable 1 * Power adapter 1 * Quick Installation Guide

## **TENDA TECHNOLOGY CO.,LTD.**

Tenda Technology Bldg.Int' I E-City,  
#1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen  
China.

E-mail: [support@tenda.com.cn](mailto:support@tenda.com.cn)  
Tel: +86-755-2765 7098  
Fax: +86-755-2765 7178  
PC: 518055