



中国认可
国际互认
检测
TESTING
CNAS L5662



ETSI EN 301 893 V2.1.1 (2017-05)

TEST REPORT

For

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen,
China. 518052

Tested Model: A23

Report Type: Original Report	Product Type: AX1500 Wi-Fi 6 Range Extender
Report Number:	DG2230214-06388E-22A
Report Date:	2023/3/15
Reviewed By:	Fay Hu Project Engineer <i>Fay Hu</i>
Approved By:	Rocky Xiao RF Engineer
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
TECHNICAL SPECIFICATION.....	5
OBJECTIVE	5
TEST METHODOLOGY.....	5
MEASUREMENT UNCERTAINTY	6
DECLARATIONS	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION.....	7
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS.....	9
BLOCK DIAGRAM OF TEST SETUP	10
TEST EQUIPMENT LIST	11
ENVIRONMENTAL CONDITIONS	12
SUMMARY OF TEST RESULTS	13
1 – CARRIER FREQUENCIES	14
DEFINITION	14
LIMIT.....	14
TEST PROCEDURE.....	14
TEST DATA.....	14
2 – NOMINAL CHANNEL BANDWIDTH AND OCCUPIED CHANNEL BANDWIDTH.....	16
DEFINITION	16
LIMIT.....	16
TEST PROCEDURE.....	16
TEST DATA.....	17
3 – RF OUTPUT POWER, TRANSMIT POWER CONTROL (TPC), POWER DENSITY	21
DEFINITION	21
LIMIT.....	21
TEST PROCEDURE.....	22
TEST DATA.....	22
4 – TRANSMITTER UNWANTED EMISSIONS OUTSIDE THE 5 GHZ RLAN BANDS	58
DEFINITION	58
LIMIT.....	58
TEST PROCEDURE.....	58
TEST DATA.....	59
5 – TRANSMITTER UNWANTED EMISSIONS WITHIN THE 5 GHZ RLAN BANDS.....	64
DEFINITION	64
LIMIT.....	64
TEST PROCEDURE.....	64
TEST DATA.....	64
6 – RECEIVER SPURIOUS EMISSIONS	77
DEFINITION	77
LIMIT.....	77
TEST PROCEDURE.....	77
TEST DATA.....	78
8 – ADAPTIVITY	83
APPLICABLE STANDARD.....	83

LIMIT..... 83
TEST PROCEDURE..... 83
BLOCK DIAGRAM OF TEST SETUP 83
TEST DATA..... 84

9 – RECEIVER BLOCKING..... 91
 APPLICABLE STANDARD..... 91
 LIMIT..... 91
 TEST PROCEDURE..... 91
 BLOCK DIAGRAM OF TEST SETUP 91
 TEST DATA..... 92

EXHIBIT A – EUT PHOTOGRAPHS 93
EXHIBIT B – TEST SET UP PHOTOGRAPHS 94

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	DG2230214-06388E-22A	Original Report	2023/3/15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name:	AX1500 Wi-Fi 6 Range Extender
Tested Model:	A23
Rated Input Voltage:	100-240Vac
Serial Number:	21C4
EUT Received Date:	2023/2/16
EUT Received Status:	Good

Technical Specification

Operation Frequency Range (MHz):	802.11 a/n20/ac20/ax20: 5180-5240 802.11 n40/ac40/ax40: 5190-5230 802.11 ac80/ax80: 5210	
RF Output Power (EIRP) (dBm):	21.62	
Number of Chains	Transmit:	2
	Receive:	2
Antenna Gain (dBi)_5.2G^▲:	4.24	
Antenna Gain (dBi)_5.3G^▲:	4.24	
Beamforming Gain (dB)^▲:	3	
Modulation Type:	OFDM, OFDMA	

Objective

This report is prepared on behalf of *SHENZHEN TENDA TECHNOLOGY CO.,LTD.* in accordance with ETSI EN 301 893 V2.1.1 (2017-05) 5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU.

The objective is to determine the compliance of EUT with: ETSI EN 301 893 V2.1.1 (2017-05).

Test Methodology

All measurements contained in this report were conducted with ETSI EN 301 893 V2.1.1 (2017-05) 5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU.

Measurement Uncertainty

Parameter	F _{lab}	Maximum allow uncertainty
RF Frequency	$\pm 1 \times 10^{-6}$	$\pm 1 \times 10^{-5}$
RF power conducted	$\pm 0.61 \text{ dB}$	$\pm 1,5 \text{ dB}$
RF power radiated	$\pm 3.62 \text{ dB}$	$\pm 6 \text{ dB}$
Spurious emissions, conducted	$\pm 2.47 \text{ dB}$	$\pm 3 \text{ dB}$
Spurious emissions, radiated	$\pm 3.62 \text{ dB}$	$\pm 6 \text{ dB}$
Temperature	$\pm 1 \text{ }^\circ\text{C}$	$\pm 2 \text{ }^\circ\text{C}$
Humidity	$\pm 5\%$	$\pm 5\%$
Time	1%	$\pm 10\%$

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode, which was provided by manufacture. The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80/ax20/ax40/ax80.

For 5150~5250 MHz band(W52), 7 channels were provided:

Frequency (MHz)	Frequency (MHz)
5180	5220
5190	5230
5200	5240
5210	/

For 5250~5350 MHz band(W53), 7 channels are provided:

Frequency (MHz)	Frequency (MHz)
5260	5300
5270	5310
5280	5320
5290	/

Test condition as below:

NT: Normal Temperature 25°C, LT: Low Temperature 0°C, HT: High Temperature +40°C

EUT Exercise Software

Software “MP_tool_8832b” was used and the power level was configured as below. The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the average power and PSD across all data rates, bandwidths, and modulations[▲].

Note: For 802.11 ax20, 802.11 ax40 and 802.11 ax80 modes, the Signal waveform level are the same, that is, the PSD of each type of RU configuration are the same. The full RU configuration was the worst, which was selected for fully test.

Mode	Frequency (MHz)	Data rate (Mbps)	Power level	
			ANT 0(Chain 0)	ANT 1(Chain 1)
802.11 a	5180	6	18	18
	5240	6	18	18
802.11 n20	5180	MCS8	15	15
	5240	MCS8	15	15
802.11 n40	5190	MCS8	14.5	15
	5230	MCS8	15	15
802.11 ac20	5180	VHTMCS8	16	16
	5240	VHTMCS8	16	16
802.11 ac40	5190	VHTMCS8	16.5	16
	5230	VHTMCS8	16.5	16.5
802.11 ac80	5210	VHTMCS8	17	17

Test Mode	Frequency (MHz)	Tones/ RU Index	Data rate (Mbps)	Power level	
				ANT 0(Chain 0)	ANT 1(Chain 1)
802.11 ax20	5180	26	HEMCS8	7	6
		52	HEMCS8	9.5	9
		106	HEMCS8	12.5	12
		242	HEMCS8	15.5	15
	5240	26	HEMCS8	7	6
		52	HEMCS8	10	9
		106	HEMCS8	13	12
		242	HEMCS8	16	15
802.11 ax40	5190	26	HEMCS8	4.5	4
		52	HEMCS8	7.5	7
		106	HEMCS8	10.5	10
		242	HEMCS8	13.5	13
		484	HEMCS8	16.5	16
	5230	26	HEMCS8	4.5	4
		52	HEMCS8	7.5	7
		106	HEMCS8	10.5	10
		242	HEMCS8	13.5	13
		484	HEMCS8	16.5	16
802.11 ax80	5210	26	HEMCS8	1.5	1
		52	HEMCS8	4.5	4
		106	HEMCS8	7.5	7
		242	HEMCS8	10.5	10
		484	HEMCS8	13.5	13
		996	HEMCS8	16.5	16

Beamforming

Mode	Frequency (MHz)	Data rate (Mbps)	Power level	
			ANT 0(Chain 0)	ANT 1(Chain 1)
802.11 n20	5180	MCS8	12	12
	5240	MCS8	12.5	12.5
802.11 n40	5190	MCS8	12	12
	5230	MCS8	12	12
802.11 ac20	5180	VHTMCS8	13.5	13
	5240	VHTMCS8	13.5	13.5
802.11 ac40	5190	VHTMCS8	13.5	13.5
	5230	VHTMCS8	14	13.5
802.11 ac80	5210	VHTMCS8	15.5	15.5

Test Mode	Frequency (MHz)	Tones/ RU Index	Data rate (Mbps)	Power level	
				ANT 0(Chain 0)	ANT 1(Chain 1)
802.11 ax20	5180	26	HEMCS8	3.5	3
		52	HEMCS8	6.5	6
		106	HEMCS8	9.5	9
		242	HEMCS8	12.5	12
	5240	26	HEMCS8	3.5	3.5
		52	HEMCS8	6.5	6.5
		106	HEMCS8	9.5	9.5
		242	HEMCS8	12.5	12.5
802.11 ax40	5190	26	HEMCS8	1	1
		52	HEMCS8	4	4
		106	HEMCS8	7	7
		242	HEMCS8	10	10
		484	HEMCS8	13	13
	5230	26	HEMCS8	1.5	1
		52	HEMCS8	4.5	4
		106	HEMCS8	7.5	7
		242	HEMCS8	10.5	10
		484	HEMCS8	13.5	13
802.11 ax80	5210	26	HEMCS8	-1	-1
		52	HEMCS8	3	3
		106	HEMCS8	5	5
		242	HEMCS8	8	8
		484	HEMCS8	11	11
		996	HEMCS8	14	14


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

Support Cable List and Details

Cable Description	Shielding Cable	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

Block Diagram of Test Setup



Test Equipment List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated emissions below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-1	2020/11/10	2023/11/9
R&S	EMI Test Receiver	ESR3	102453	2022/11/18	2023/11/17
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2022/7/19	2023/7/18
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2022/7/19	2023/7/18
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2022/7/19	2023/7/18
Sonoma	Amplifier	310N	372193	2022/7/18	2023/7/17
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2022/9/4	2023/9/3
Agilent	Signal Generator	E8247C	MY43321350	2022/4/1	2023/3/31
Radiated emissions above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2021/10/12	2024/10/11
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020/12/5	2023/12/4
Agilent	Spectrum Analyzer	E4440A	SG43360054	2022/7/15	2023/7/14
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2022/9/4	2023/9/3
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2022/6/27	2023/6/26
AH	Preamplifier	PAM-0118	469	2022/10/13	2023/10/12
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2022/6/27	2023/6/26
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2022/5/18	2025/5/17
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2020/12/5	2023/12/4
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2022/9/4	2023/9/3
Agilent	Signal Generator	E8247C	MY43321350	2022/4/1	2023/3/31
Mini Circuits	High Pass Filter	VHF-6010+	31118	2022/6/16	2023/6/15
RF conducted					
R&S	Spectrum Analyzer	FSV40	101589	2022/11/22	2023/11/21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	OE01201047	2022/5/6	2023/5/5
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	2022/9/4	2023/9/3
Agilent	USB Wideband Power Sensor	U2022XA	MY54170006	2022/11/22	2023/11/21
R&S	Wideband Radio Communication Tester	CMW500	149216	2022/11/18	2023/11/17
BACL	TEMP&HUMI Test Chamber	BTH-150	30022	2022/11/18	2023/11/17
Keysight	MXA Signal Analyzer	N9020A	MY48490137	2022/11/16	2023/11/15
Agilent	MXG Analog Signal Generator	N5181A	MY48180151	2022/11/18	2023/11/17
Agilent	MXG Vector Signal Generator	N5182A	MY49060274	2022/11/18	2023/11/17
Tonscend	RF Control Unit	JS0806-2	19G8060171	2022/11/16	2023/11/15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Environmental Conditions

Test Item:	Radiated emissions (below 1GHz)	Radiated emissions (above 1GHz)	RF conducted
Temperature:	20.8 °C	21.8 °C	22.8~23.5°C
Relative Humidity:	37.0 %	42.0 %	49~60%
ATM Pressure:	102.3 kPa	101.7 kPa	101.3~102kPa
Tester:	Colin Yang	Lucky Lu	Fan Fan
Test Date:	2023/2/17	2023/2/22	2023/2/19~2023/2/20

SUMMARY OF TEST RESULTS

SN	Rule and Clause	Description of Test	Test Result
1	EN 301 893 Clause 4.2.1	Carrier frequencies	Compliant
2	EN 301 893 Clause 4.2.2	Nominal channel bandwidth and occupied channel bandwidth	Compliant
3	EN 301 893 Clause 4.2.3	RF output power	Compliant
		Transmit power control (TPC)	Not applicable*
		Power Density	Compliant
4	EN 301 893 Clause 4.2.4.1	Transmitter unwanted emissions outside the 5 GHz RLAN bands	Compliant
5	EN 301 893 Clause 4.2.4.2	Transmitter unwanted emissions within the 5 GHz RLAN bands	Compliant
6	EN 301 893 Clause 4.2.5	Receiver spurious emissions	Compliant
7	EN 301 893 Clause 4.2.6	Dynamic frequency selection (DFS)	Not applicable**
8	EN 301 893 Clause 4.2.7	Adaptivity	Compliant
9	EN 301 893 Clause 4.2.8	Receiver blocking	Compliant
10	EN 301 893 Clause 4.2.9	User access restrictions	Compliant*
11	EN 301 893 Clause 4.2.10	Geo-location capability	Not applicable*

Note:

Not applicable*: The device without this function.

Not applicable:** The device do not works on DFS band.

Compliant*: Please refer to the product information declared by the manufacturer.

1 – CARRIER FREQUENCIES

Definition

The Nominal Centre Frequency is the centre of the Operating Channel.

Limit

The actual centre frequency for any given channel declared by the manufacturer shall be maintained within the range $f_c \pm 20$ ppm.

Test Procedure

According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.2


Test Data

Test Result: Compliant. Please refer to following table(s) and Plot(s).

Band (MHz)	Fc (MHz)	Test Condition	F (MHz)	Result (ppm)	Limit (ppm)
5150-5250	5180	NT	5180.00781	1.51	± 20
		LT	5180.00789	1.52	
		HT	5180.00778	1.50	
	5240	NT	5240.00781	1.49	± 20
		LT	5240.00788	1.50	
		HT	5240.00777	1.48	


The Normal condition test plots, please refer to following Plots:

5180



Date: 19.FEB.2023 16:00:13

5240



Date: 19.FEB.2023 16:00:59

2 – NOMINAL CHANNEL BANDWIDTH AND OCCUPIED CHANNEL BANDWIDTH

Definition

The Nominal Channel Bandwidth is the widest band of frequencies, inclusive of guard bands, assigned to a single channel.

The Occupied Channel Bandwidth is the bandwidth containing 99 % of the power of the signal.

When equipment has simultaneous transmissions in adjacent channels, these transmissions may be considered as one signal with an actual Nominal Channel Bandwidth of 'n' times the individual Nominal Channel Bandwidth where 'n' is the number of adjacent channels. When equipment has simultaneous transmissions in non-adjacent channels, each power envelope shall be considered separately.

Limit

The Nominal Channel Bandwidth for a single Operating Channel shall be 20 MHz.

Alternatively, equipment may implement a lower Nominal Channel Bandwidth with a minimum of 5 MHz, providing they still comply with the Nominal Centre Frequencies defined in clause 4.2.1 (20 MHz raster). The Occupied Channel Bandwidth shall be between 80 % and 100 % of the Nominal Channel Bandwidth. In case of smart antenna systems (devices with multiple transmit chains) each of the transmit chains shall meet this requirement.

The Occupied Channel Bandwidth might change with time/payload.

During a Channel Occupancy Time (COT), equipment may operate temporarily with an Occupied Channel Bandwidth of less than 80 % of its Nominal Channel Bandwidth with a minimum of 2 MHz.

Test Procedure


According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.3

Test Data

Test Result: Compliant. Please refer to following table(s) and Plot(s).


Band (MHz)	Mode	Fc (MHz)	Nominal Channel Bandwidth (MHz)	Result (MHz)	Limit (MHz)
5150-5250	802.11 a	5180	20	16.27	16~20
		5240	20	16.21	16~20
	802.11 n20	5180	20	17.42	16~20
		5240	20	17.42	16~20
	802.11 n40	5190	40	35.77	32~40
		5230	40	35.77	32~40
	802.11 ac20	5180	20	17.48	16~20
		5240	20	17.48	16~20
	802.11 ac40	5190	40	36.01	32~40
		5230	40	36.12	32~40
	802.11 ac80	5210	80	75.48	64~80
	802.11 ax20	5180	20	18.76	16~20
		5240	20	18.81	16~20
	802.11 ax40	5190	40	37.63	32~40
		5230	40	37.63	32~40
	802.11 ax80	5210	80	76.64	64~80

802.11 a Low




Date: 19.FEB.2023 16:03:15

802.11 a High




Date: 19.FEB.2023 16:07:18

802.11 n20 Low




Date: 19.FEB.2023 16:12:00

802.11 n20 High




Date: 19.FEB.2023 16:08:03

802.11 n40 Low




Date: 19.FEB.2023 16:48:01

802.11 n40 High




Date: 19.FEB.2023 16:47:22


802.11 ac20 Low




802.11 ac20 High




802.11 ac40 Low




802.11 ac40 High



802.11 ac80




802.11 ax20 Low




Date: 19.FEB.2023 16:32:57

802.11 ax20 High




Date: 19.FEB.2023 16:32:20

802.11 ax40 Low




Date: 19.FEB.2023 17:12:40

802.11 ax40 High



Date: 19.FEB.2023 17:12:02

802.11 ax80



Date: 19.FEB.2023 17:25:40

3 – RF OUTPUT POWER, TRANSMIT POWER CONTROL (TPC), POWER DENSITY

Definition

RF Output Power:

The RF Output Power is the mean equivalent isotropically radiated power (e.i.r.p.) during a transmission burst.

Transmit Power Control (TPC):

Transmit Power Control (TPC) is a mechanism to be used by the RLAN device to ensure a mitigation factor of at least 3 dB on the aggregate power from a large number of devices. This requires the RLAN device to have a TPC range from which the lowest value is at least 6 dB below the values for mean e.i.r.p. given in table 2 for devices with TPC.

Power Density:

The Power Density is the mean Equivalent Isotropically Radiated Power (e.i.r.p.) density during a transmission burst.

Limit

TPC is not required for channels whose nominal bandwidth falls completely within the band 5150 MHz to 5250 MH.

For devices with TPC, the RF output power and the power density when configured to operate at the highest stated power level of the TPC range shall not exceed the levels given in table 2.

Devices are allowed to operate without TPC. See table 2 for the applicable limits in this case.

Table 2: Mean e.i.r.p. limits for RF output power and Power Density at the highest power level (P_H)

Frequency range (MHz)	Mean e.i.r.p. limit for P _H (dBm)		Mean e.i.r.p. density limit (dBm/MHz)	
	with TPC	without TPC	with TPC	without TPC
5 150 to 5 350	23	20/23 (see note 1)	10	7/10 (see note 2)
5 470 to 5 725	30 (see note 3)	27 (see note 3)	17 (see note 3)	14 (see note 3)

NOTE 1: The applicable limit is 20 dBm, except for transmissions whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz, in which case the applicable limit is 23 dBm.

NOTE 2: The applicable limit is 7 dBm/MHz, except for transmissions whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz, in which case the applicable limit is 10 dBm/MHz.

NOTE 3: Slave devices without a *Radar Interference Detection* function shall comply with the limits for the frequency range 5 250 MHz to 5 350 MHz.

Table 3: Mean e.i.r.p. limits for RF Output Power at the lowest power level of the TPC range

Frequency range	Mean e.i.r.p. (dBm) limit for P _L
5 250 MHz to 5 350 MHz	17
5 470 MHz to 5 725 MHz	24 (see note)
NOTE: Slave devices without a <i>Radar Interference Detection</i> function shall comply with the limits for the band 5 250 MHz to 5 350 MHz.	

Test Procedure

According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.4

Test Data

Test Result: Compliant. Please refer to following table(s).

Test Mode	Test Condition	Fc (MHz)	Conducted output power (dBm)		Result_EIRP (dBm)		Limit (dBm)
			Chain 0	Chain 1	Chain 0	Chain 1	
802.11 a	NT	5180	16.63	16.36	20.87	20.60	≤ 23
		5240	16.47	16.22	20.71	20.46	≤ 23
	LT	5180	17.38	17.27	21.62	21.51	≤ 23
		5240	17.25	17.16	21.49	21.40	≤ 23
	HT	5180	15.89	15.85	20.13	20.09	≤ 23
		5240	15.76	15.78	20.00	20.02	≤ 23

Test Mode	Test Condition	Fc (MHz)	Conducted output power (dBm)		Result_EIRP (dBm)	Limit (dBm)
			Chain 0	Chain 1	Total	
802.11 n20	NT	5180	13.52	13.27	20.65	≤ 23
		5240	13.33	13.05	20.44	≤ 23
	LT	5180	14.23	13.89	21.31	≤ 23
		5240	13.87	13.78	21.08	≤ 23
	HT	5180	13.15	12.92	20.29	≤ 23
		5240	12.86	12.76	20.06	≤ 23
802.11 n40	NT	5190	13.41	13.27	20.59	≤ 23
		5230	13.53	13.34	20.69	≤ 23
	LT	5190	14.23	13.85	21.29	≤ 23
		5230	14.38	13.96	21.43	≤ 23
	HT	5190	13.06	12.77	20.17	≤ 23
		5230	13.12	12.85	20.24	≤ 23
802.11 ac20	NT	5180	13.24	13.19	20.47	≤ 23
		5240	13.38	13.41	20.65	≤ 23
	LT	5180	13.78	13.84	21.06	≤ 23
		5240	13.89	14.26	21.33	≤ 23
	HT	5180	12.67	12.85	20.01	≤ 23
		5240	12.76	13.03	20.15	≤ 23
802.11 ac40	NT	5190	13.72	13.01	20.63	≤ 23
		5230	13.57	13.36	20.72	≤ 23
	LT	5190	14.58	13.87	21.49	≤ 23
		5230	14.63	13.96	21.56	≤ 23
	HT	5190	13.15	12.68	20.17	≤ 23
		5230	13.03	12.85	20.19	≤ 23
802.11 ac80	NT	5210	13.40	12.99	20.45	≤ 23
	LT	5210	14.26	13.68	21.23	≤ 23
	HT	5210	13.03	12.24	19.90	≤ 23

Test Mode	Test Condition	Fc (MHz)	Tones/ RU Index	Conducted output power (dBm)		Result EIRP (dBm)	Limit (dBm)
				Chain 0	Chain 1	Total	
802.11 ax20	NT	5180	26/0	4.35	3.82	11.34	≤ 23
			52/37	7.43	6.94	14.44	≤ 23
			106/53	10.51	10.06	17.54	≤ 23
			242/61	13.60	13.15	20.63	≤ 23
		5240	26/8	4.41	3.73	11.33	≤ 23
			52/40	7.54	6.87	14.47	≤ 23
			106/54	10.63	9.95	17.55	≤ 23
			242/61	13.78	13.02	20.67	≤ 23
802.11 ax20	LT	5180	26/0	4.44	3.88	11.42	≤ 23
			52/37	7.64	7.03	14.60	≤ 23
			106/53	10.75	10.36	17.81	≤ 23
			242/61	13.72	13.45	20.84	≤ 23
		5240	26/8	4.68	3.94	11.58	≤ 23
			52/40	7.78	7.17	14.74	≤ 23
			106/54	10.81	10.04	17.69	≤ 23
			242/61	14.02	13.29	20.92	≤ 23
802.11 ax20	HT	5180	26/0	4.23	3.52	11.14	≤ 23
			52/37	7.37	6.76	14.33	≤ 23
			106/53	10.21	9.82	17.27	≤ 23
			242/61	13.51	12.94	20.48	≤ 23
		5240	26/8	4.11	3.46	11.05	≤ 23
			52/40	7.24	6.57	14.17	≤ 23
			106/54	10.33	9.86	17.35	≤ 23
			242/61	13.57	12.99	20.54	≤ 23

Test Mode	Test Condition	Fc (MHz)	Tones/ RU Index	Conducted output power (dBm)		Result EIRP (dBm)	Limit (dBm)
				Chain 0	Chain 1	Total	
802.11 ax40	NT	5190	26/0	1.51	1.00	8.51	≤ 23
			52/37	4.64	4.02	11.59	≤ 23
			106/53	7.77	7.16	14.73	≤ 23
			242/61	10.82	10.25	17.79	≤ 23
			484/65	13.95	13.32	20.90	≤ 23
		5230	26/17	1.43	0.74	8.35	≤ 23
			52/44	4.51	3.81	11.42	≤ 23
			106/56	7.64	6.94	14.55	≤ 23
			242/62	10.72	10.05	17.65	≤ 23
			484/65	13.87	13.16	20.78	≤ 23
802.11 ax40	LT	5190	26/0	1.60	1.27	8.69	≤ 23
			52/37	4.73	4.14	11.70	≤ 23
			106/53	7.83	7.22	14.79	≤ 23
			242/61	11.00	10.31	17.92	≤ 23
			484/65	13.98	13.44	20.97	≤ 23
		5230	26/17	1.49	1.01	8.51	≤ 23
			52/44	4.63	3.87	11.52	≤ 23
			106/56	7.79	7.15	14.73	≤ 23
			242/62	10.78	10.08	17.69	≤ 23
			484/65	14.17	13.22	20.97	≤ 23
802.11 ax40	HT	5190	26/0	1.48	0.76	8.39	≤ 23
			52/37	4.52	3.99	11.51	≤ 23
			106/53	7.47	7.10	14.54	≤ 23
			242/61	10.76	10.13	17.71	≤ 23
			484/65	13.65	13.23	20.70	≤ 23
		5230	26/17	1.34	0.47	8.18	≤ 23
			52/44	4.33	3.57	11.22	≤ 23
			106/56	7.52	6.79	14.42	≤ 23
			242/62	10.57	9.90	17.50	≤ 23
			484/65	13.75	12.98	20.63	≤ 23

Test Mode	Test Condition	Fc (MHz)	Tones/RU Index	Conducted output power (dBm)		Result EIRP (dBm)	Limit (dBm)
				Chain 0	Chain 1	Total	
802.11 ax80	NT	5210	26/0	-3.13	-2.48	4.46	≤ 23
			52/37	0.02	0.61	7.58	≤ 23
			106/53	3.06	3.72	10.65	≤ 23
			242/61	7.13	6.85	14.24	≤ 23
			484/65	10.21	9.94	17.33	≤ 23
			996/67	13.34	13.03	20.44	≤ 23
802.11 ax80	LT	5210	26/0	-3.07	-2.33	4.57	≤ 23
			52/37	0.32	0.70	7.76	≤ 23
			106/53	3.15	4.02	10.86	≤ 23
			242/61	7.37	7.06	14.47	≤ 23
			484/65	10.45	10.12	17.54	≤ 23
			996/67	13.74	13.67	20.96	≤ 23
802.11 ax80	HT	5210	26/0	-3.31	-2.60	4.31	≤ 23
			52/37	-0.04	0.49	7.48	≤ 23
			106/53	2.91	3.54	10.49	≤ 23
			242/61	6.92	6.55	13.99	≤ 23
			484/65	9.97	9.85	17.16	≤ 23
			996/67	13.22	12.85	20.29	≤ 23

Beamforming:

Test Mode	Test Condition	Fc (MHz)	Conducted output power (dBm)		Result_EIRP (dBm)	Limit (dBm)
			Chain 0	Chain 1	Total	
802.11 n20	NT	5180	10.23	10.03	20.38	≤ 23
		5240	10.26	10.16	20.46	≤ 23
	LT	5180	10.86	10.78	21.07	≤ 23
		5240	10.89	10.89	21.14	≤ 23
	HT	5180	9.74	9.54	19.89	≤ 23
		5240	9.68	9.67	19.93	≤ 23
802.11 n40	NT	5190	10.65	10.37	20.76	≤ 23
		5230	10.36	10.20	20.53	≤ 23
	LT	5190	11.56	10.87	21.48	≤ 23
		5230	10.89	10.68	21.04	≤ 23
	HT	5190	9.67	9.82	20.00	≤ 23
		5230	9.48	9.74	19.86	≤ 23
802.11 ac20	NT	5180	10.81	10.16	20.75	≤ 23
		5240	10.09	10.56	20.58	≤ 23
	LT	5180	11.74	10.89	21.59	≤ 23
		5240	10.87	11.34	21.36	≤ 23
	HT	5180	10.18	9.83	20.26	≤ 23
		5240	9.74	10.05	20.15	≤ 23
802.11 ac40	NT	5190	10.66	10.19	20.68	≤ 23
		5230	10.97	9.14	20.40	≤ 23
	LT	5190	11.35	10.82	21.34	≤ 23
		5230	11.57	9.89	21.06	≤ 23
	HT	5190	10.07	9.57	20.08	≤ 23
		5230	10.16	8.78	19.77	≤ 23
802.11 ac80	NT	5210	10.52	10.36	20.69	≤ 23
	LT	5210	11.36	10.89	21.38	≤ 23
	HT	5210	10.02	9.74	20.13	≤ 23

Test Mode	Test Condition	Fc (MHz)	Tones/ RU Index	Conducted output power (dBm)		Result EIRP (dBm)	Limit (dBm)
				Chain 0	Chain 1	Total	
802.11 ax20	NT	5180	26/0	1.15	0.71	11.19	≤ 23
			52/37	4.24	3.84	14.29	≤ 23
			106/53	7.32	6.96	17.39	≤ 23
			242/61	10.48	10.07	20.53	≤ 23
		5240	26/8	0.83	1.06	11.20	≤ 23
			52/40	3.92	4.18	14.30	≤ 23
			106/54	7.06	7.31	17.44	≤ 23
			242/61	10.14	10.40	20.52	≤ 23
802.11 ax20	LT	5180	26/0	1.30	0.86	11.34	≤ 23
			52/37	4.30	4.08	14.44	≤ 23
			106/53	7.44	7.02	17.49	≤ 23
			242/61	10.57	10.10	20.59	≤ 23
		5240	26/8	0.98	1.21	11.35	≤ 23
			52/40	4.16	4.30	14.48	≤ 23
			106/54	7.33	7.55	17.69	≤ 23
			242/61	10.23	10.64	20.69	≤ 23
802.11 ax20	HT	5180	26/0	1.09	0.59	11.10	≤ 23
			52/37	4.15	3.72	14.19	≤ 23
			106/53	7.11	6.69	17.16	≤ 23
			242/61	10.45	9.77	20.37	≤ 23
		5240	26/8	0.77	1.00	11.14	≤ 23
			52/40	3.77	4.12	14.20	≤ 23
			106/54	6.79	7.25	17.28	≤ 23
			242/61	10.05	10.22	20.39	≤ 23

Test Mode	Test Condition	Fc (MHz)	Tones/RU Index	Conducted output power (dBm)		Result_EIRP (dBm)	Limit (dBm)
				Chain 0	Chain 1	Total	
802.11 ax40	NT	5190	26/0	-2.17	-2.19	8.07	≤ 23
			52/37	1.02	0.87	11.20	≤ 23
			106/53	4.13	3.95	14.29	≤ 23
			242/61	7.21	7.02	17.37	≤ 23
			484/65	10.35	10.10	20.48	≤ 23
		5230	26/17	-1.87	-2.38	8.13	≤ 23
			52/44	1.26	0.74	11.26	≤ 23
			106/56	4.32	3.82	14.33	≤ 23
			242/62	7.45	6.94	17.45	≤ 23
			484/65	10.58	10.07	20.58	≤ 23
802.11 ax40	LT	5190	26/0	-1.87	-2.13	8.25	≤ 23
			52/37	1.14	1.02	11.33	≤ 23
			106/53	4.31	4.16	14.49	≤ 23
			242/61	7.27	7.26	17.52	≤ 23
			484/65	10.65	10.31	20.73	≤ 23
		5230	26/17	-1.69	-2.23	8.30	≤ 23
			52/44	1.56	0.77	11.43	≤ 23
			106/56	4.53	3.97	14.51	≤ 23
			242/62	7.63	7.12	17.63	≤ 23
			484/65	10.64	10.28	20.71	≤ 23
802.11 ax40	HT	5190	26/0	-2.23	-2.46	7.91	≤ 23
			52/37	0.84	0.63	10.99	≤ 23
			106/53	3.92	3.71	14.07	≤ 23
			242/61	7.09	6.90	17.25	≤ 23
			484/65	10.23	9.92	20.33	≤ 23
		5230	26/17	-1.99	-2.50	8.01	≤ 23
			52/44	1.08	0.56	11.08	≤ 23
			106/56	4.02	3.58	14.06	≤ 23
			242/62	7.15	6.67	17.17	≤ 23
			484/65	10.28	9.95	20.37	≤ 23

Test Mode	Test Condition	Fc (MHz)	Tones/ RU Index	Conducted output power (dBm)		Result_EIRP (dBm)	Limit (dBm)
				Chain 0	Chain 1	Total	
802.11 ax80	NT	5210	26/0	-5.18	-5.06	5.13	≤ 23
			52/37	-2.07	-1.97	8.23	≤ 23
			106/53	1.03	1.16	11.35	≤ 23
			242/61	4.11	4.28	14.45	≤ 23
			484/65	7.24	7.36	17.55	≤ 23
			996/67	10.31	10.45	20.63	≤ 23
802.11 ax80	LT	5210	26/0	-4.93	-4.97	5.30	≤ 23
			52/37	-1.77	-1.79	8.47	≤ 23
			106/53	1.06	1.28	11.42	≤ 23
			242/61	4.29	4.58	14.69	≤ 23
			484/65	7.39	7.60	17.75	≤ 23
			996/67	10.34	10.60	20.72	≤ 23
802.11 ax80	HT	5210	26/0	-5.21	-5.24	5.03	≤ 23
			52/37	-2.10	-2.21	8.10	≤ 23
			106/53	0.82	0.95	11.14	≤ 23
			242/61	3.99	3.98	14.24	≤ 23
			484/65	7.06	7.12	17.34	≤ 23
			996/67	10.04	10.15	20.35	≤ 23

Note: The antenna Gain was added into the result.

Power Density

Band (MHz)	Mode	Fc (MHz)	Conducted power density (dBm/MHz)		Result (dBm/MHz)		Limit (dBm/MHz)
			Chain 0	Chain 1	Chain 0	Chain 1	
5150-5250	802.11 a	5180	5.37	4.88	9.88	9.39	10
		5240	4.94	4.60	9.45	9.11	10
	802.11 n20	5180	1.64	1.13	9.10		10
		5240	1.18	0.85	8.73		10
	802.11 n40	5190	-2.09	-1.99	6.18		10
		5230	-1.84	-2.04	6.28		10
	802.11 ac20	5180	-0.71	-0.71	9.33		10
		5240	-1.16	-1.05	8.94		10
	802.11 ac40	5190	-3.56	-4.53	6.50		10
		5230	-3.95	-4.05	6.52		10
802.11 ac80	5210	-6.40	-6.73	4.95		10	
5150-5250	802.11 ax20	5180	-0.51	-0.70	9.25		≤ 10
			-0.45	-0.62	9.32		≤ 10
			-0.39	-0.52	9.40		≤ 10
			-0.57	-0.72	9.21		≤ 10
		5240	-0.52	-0.94	9.13		≤ 10
			-0.36	-0.96	9.20		≤ 10
			-0.50	-0.88	9.16		≤ 10
			-0.56	-1.04	9.06		≤ 10
	802.11 ax40	5190	-3.65	-4.11	6.90		≤ 10
			-3.59	-4.13	6.92		≤ 10
			-3.51	-4.15	6.95		≤ 10
			-3.55	-4.09	6.96		≤ 10
		5230	-3.69	-4.19	6.84		≤ 10
			-3.91	-4.37	6.64		≤ 10
			-3.89	-4.43	6.62		≤ 10
			-3.93	-4.43	6.60		≤ 10
	802.11 ax80	5210	-3.89	-4.33	6.67		≤ 10
			-4.05	-4.47	6.52		≤ 10
			-6.98	-7.26	3.98		≤ 10
			-7.06	-7.21	3.97		≤ 10
		5210	-7.13	-7.18	3.95		≤ 10
			-7.06	-7.28	3.93		≤ 10
			-7.02	-7.23	3.98		≤ 10
			-7.07	-7.15	3.99		≤ 10

Beamforming:

Band (MHz)	Mode	Fc (MHz)	Conducted power density (dBm/MHz)		Result (dBm/MHz)		Limit (dBm/MHz)
			Chain 0	Chain 1	Chain 0	Chain 1	
5150-5250	802.11 n20	5180	-1.36	-1.84	9.12		10
		5240	-1.98	-1.75	8.85		10
	802.11 n40	5190	-4.55	-4.96	6.47		10
		5230	-4.95	-5.09	6.20		10
	802.11 ac20	5180	-3.28	-3.86	9.48		10
		5240	-3.82	-3.66	9.30		10
	802.11 ac40	5190	-6.57	-7.06	6.71		10
		5230	-6.47	-7.15	6.72		10
	802.11 ac80	5210	-7.94	-8.26	6.41		10
	5150-5250	802.11 ax20	5180	-3.53	-3.75	9.21	
-3.48				-3.70	9.26		≤ 10
-3.44				-3.78	9.24		≤ 10
-3.60				-3.78	9.16		≤ 10
5240			-4.05	-3.40	9.14		≤ 10
			-4.15	-3.54	9.02		≤ 10
			-3.97	-3.44	9.15		≤ 10
			-4.17	-3.56	9.00		≤ 10
802.11 ax40		5190	-7.05	-7.23	6.63		≤ 10
			-7.21	-7.21	6.56		≤ 10
			-7.19	-7.11	6.62		≤ 10
			-7.23	-7.15	6.58		≤ 10
		5230	-7.25	-7.25	6.52		≤ 10
			-7.11	-7.43	6.50		≤ 10
			-7.05	-7.31	6.59		≤ 10
			-6.97	-7.43	6.58		≤ 10
802.11 ax80		5210	-7.09	-7.35	6.55		≤ 10
			-7.15	-7.49	6.45		≤ 10
			-9.49	-8.84	4.95		≤ 10
			-9.47	-8.78	4.99		≤ 10
			-9.45	-8.88	4.94		≤ 10
			-9.45	-8.92	4.92		≤ 10
		-9.55	-8.78	4.95		≤ 10	
		-9.65	-8.94	4.82		≤ 10	

Note:

1, The antenna gain and duty cycle factor were added into the result.


2, Duty cycle factor = $10 \cdot \log(1/\text{duty cycle})$

Duty Cycle:

Mode	Ton (ms)	Ton+Toff (ms)	Duty cycle (%)	Duty cycle Factor (dB)
802.11 a	1.39	1.48	93.92	0.27
802.11 n20	0.63	0.70	90.00	0.46
802.11 n40	0.32	0.40	80.00	0.97
802.11 ac20	0.10	0.19	52.63	2.79
802.11 ac40	0.08	0.17	47.06	3.27
802.11 ac80	0.06	0.16	37.50	4.26
802.11 ax20	0.11	0.20	55.00	2.60
802.11 ax40	0.08	0.18	44.44	3.52
802.11 ax80	0.07	0.17	41.18	3.85


Duty Cycle:

802.11 a




Date: 19.FEB.2023 16:03:02

802.11 n20




Date: 19.FEB.2023 16:12:46

802.11 n40




Date: 19.FEB.2023 16:48:58

802.11 ac20




Date: 19.FEB.2023 16:27:40

802.11 ac40




Date: 19.FEB.2023 16:52:08

802.11 ac80




Date: 19.FEB.2023 17:16:54

802.11 ax20




Date: 19.FEB.2023 16:13:49

802.11 ax40



Date: 19.FEB.2023 17:13:11


802.11 ax80




Date: 19.FEB.2023 17:26:21

PSD:
Chain0-5.2G

802.11 a-5180 MHz




Date: 19.FEB.2023 16:03:37




Date: 19.FEB.2023 16:05:06

802.11 a-5240 MHz




Date: 19.FEB.2023 16:05:37




Date: 19.FEB.2023 16:07:02

802.11 n20-5180 MHz





Date: 19.FEB.2023 16:10:32





Date: 19.FEB.2023 16:11:45



802.11 n20-5240 MHz




802.11 n40-5190 MHz




802.11 n40-5230 MHz



802.11 ac20-5180 MHz




Date: 19.FEB.2023 16:24:35




Date: 19.FEB.2023 16:25:45

802.11 ac20-5240 MHz




Date: 19.FEB.2023 16:28:42




Date: 19.FEB.2023 16:30:05

802.11 ac40-5190 MHz



Date: 19.FEB.2023 16:52:36




Date: 19.FEB.2023 16:53:50

802.11 ac40-5230 MHz




Date: 19.FEB.2023 16:54:22




Date: 19.FEB.2023 16:55:43

802.11 ac80-5210 MHz




Date: 19.FEB.2023 17:17:52




Date: 19.FEB.2023 17:19:09

802.11 ax20-5180 MHz




Date: 19.FEB.2023 16:33:15




Date: 19.FEB.2023 16:35:23

802.11 ax20-5240 MHz




Date: 19.FEB.2023 16:30:49



Date: 19.FEB.2023 16:32:07

802.11 ax40-5190 MHz




Date: 19.FEB.2023 17:13:34




Date: 19.FEB.2023 17:14:52

802.11 ax40-5230 MHz




Date: 19.FEB.2023 17:08:42




Date: 19.FEB.2023 17:11:51

802.11 ax80-5210 MHz



Date: 19.FEB.2023 17:24:02




Date: 19.FEB.2023 17:25:26

Chain1-5.2G

802.11 a-5180 MHz




Date: 19.FEB.2023 17:45:16




Date: 19.FEB.2023 17:46:36

802.11 a-5240 MHz



Date: 19.FEB.2023 17:47:13




Date: 19.FEB.2023 17:48:28

802.11 n20-5180 MHz




Date: 20.FEB.2023 19:28:21



Date: 20.FEB.2023 19:29:37



802.11 n20-5240 MHz



Date: 20.FEB.2023 19:30:18

Date: 20.FEB.2023 19:31:44



802.11 n40-5190 MHz



Date: 20.FEB.2023 20:10:25

Date: 20.FEB.2023 20:11:38



802.11 n40-5230 MHz



Date: 20.FEB.2023 20:08:48

Date: 20.FEB.2023 20:09:59



802.11 ac20-5180 MHz



Date: 20.FEB.2023 19:45:53

Date: 20.FEB.2023 19:48:15


802.11 ac20-5240 MHz



Date: 20.FEB.2023 19:43:47

Date: 20.FEB.2023 19:45:15


802.11 ac40-5190 MHz




Date: 20.FEB.2023 20:14:29

Date: 20.FEB.2023 20:16:45

802.11 ac40-5230 MHz




Date: 20.FEB.2023 20:17:29




Date: 20.FEB.2023 20:22:04

802.11 ac80-5210 MHz




Date: 19.FEB.2023 17:42:58



Date: 19.FEB.2023 17:44:16



802.11 ax20-5180 MHz



Date: 20.FEB.2023 19:52:33

Date: 20.FEB.2023 19:55:30



802.11 ax20-5240 MHz



Date: 20.FEB.2023 19:56:12

Date: 20.FEB.2023 19:57:24



802.11 ax40-5190 MHz



Date: 20.FEB.2023 20:34:47

Date: 20.FEB.2023 20:35:55



802.11 ax40-5230 MHz



Date: 20.FEB.2023 20:33:15

Date: 20.FEB.2023 20:34:22

802.11 ax80-5210 MHz





Date: 19.FEB.2023 17:37:26


Date: 19.FEB.2023 17:38:38

Beamforming Chain0-5.2G



802.11 n20-5180 MHz




802.11 n20-5320 MHz




802.11 n40-5190 MHz



802.11 n40-5230 MHz




Date: 19.FEB.2023 16:44:09




Date: 19.FEB.2023 16:45:22

802.11 ac20-5180 MHz




Date: 19.FEB.2023 16:22:49




Date: 19.FEB.2023 16:24:03

802.11 ac20-5240 MHz





Date: 19.FEB.2023 16:21:02



Date: 19.FEB.2023 16:22:17



802.11 ac40-5190 MHz



Date: 19.FEB.2023 16:58:36

Date: 19.FEB.2023 16:59:54



802.11 ac40-5230 MHz



Date: 19.FEB.2023 16:56:44

Date: 19.FEB.2023 16:57:59

802.11 ac80-5210 MHz




Date: 19.FEB.2023 17:19:39

Date: 19.FEB.2023 17:20:55

802.11 ax20-5180 MHz




Date: 19.FEB.2023 16:37:37




Date: 19.FEB.2023 16:39:24

802.11 ax20-5240 MHz





Date: 19.FEB.2023 16:39:52





Date: 19.FEB.2023 16:41:06



802.11 ax40-5190 MHz



802.11 ax40-5230 MHz



802.11 ax80-5210 MHz




Chain1-5.2G

802.11 n20-5180 MHz




Date: 20.FEB.2023 19:34:56




Date: 20.FEB.2023 19:36:31

802.11 n20-5240 MHz




Date: 20.FEB.2023 19:32:49




Date: 20.FEB.2023 19:34:15

802.11 n40-5190 MHz





Date: 20.FEB.2023 20:05:03



Date: 20.FEB.2023 20:06:18



802.11 n40-5230 MHz



Date: 20.FEB.2023 20:06:42

Date: 20.FEB.2023 20:08:13



802.11 ac20-5180 MHz



Date: 20.FEB.2023 19:38:16

Date: 20.FEB.2023 19:40:00



802.11 ac20-5240 MHz



Date: 20.FEB.2023 19:40:40

Date: 20.FEB.2023 19:43:13



802.11 ac40-5190 MHz



Date: 20.FEB.2023 20:24:38

Date: 20.FEB.2023 20:27:50



802.11 ac40-5230 MHz



Date: 20.FEB.2023 20:22:43

Date: 20.FEB.2023 20:24:06



802.11 ac80-5210 MHz



Date: 19.FEB.2023 17:41:07

Date: 19.FEB.2023 17:42:24



802.11 ax20-5180 MHz



Date: 20.FEB.2023 20:00:05

Date: 20.FEB.2023 20:03:24



802.11 ax20-5240 MHz



Date: 20.FEB.2023 19:58:13

Date: 20.FEB.2023 19:59:25



802.11 ax40-5190 MHz



Date: 20.FEB.2023 20:28:50

Date: 20.FEB.2023 20:30:17



802.11 ax40-5230 MHz



Date: 20.FEB.2023 20:30:43

Date: 20.FEB.2023 20:31:58

802.11 ax80-5210 MHz



Date: 19.FEB.2023 17:39:09

Date: 19.FEB.2023 17:40:21

4 – TRANSMITTER UNWANTED EMISSIONS OUTSIDE THE 5 GHZ RLAN BANDS

Definition

Transmitter unwanted emissions outside the 5 GHz RLAN bands are radio frequency emissions outside the 5 GHz RLAN bands defined in clause 3.1.

Limit

The level of transmitter unwanted emissions outside the 5 GHz RLAN bands shall not exceed the limits given in table 4.

Table 4: Transmitter unwanted emission limits outside the 5 GHz RLAN bands

Frequency range	Maximum power	Bandwidth
30 MHz to 47 MHz	-36 dBm	100 kHz
47 MHz to 74 MHz	-54 dBm	100 kHz
74 MHz to 87,5 MHz	-36 dBm	100 kHz
87,5 MHz to 118 MHz	-54 dBm	100 kHz
118 MHz to 174 MHz	-36 dBm	100 kHz
174 MHz to 230 MHz	-54 dBm	100 kHz
230 MHz to 470 MHz	-36 dBm	100 kHz
470 MHz to 862 MHz	-54 dBm	100 kHz
862 MHz to 1 GHz	-36 dBm	100 kHz
1 GHz to 5,15 GHz	-30 dBm	1 MHz
5,35 GHz to 5,47 GHz	-30 dBm	1 MHz
5,725 GHz to 26 GHz	-30 dBm	1 MHz

Test Procedure

According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.5

Test Data

Test Result: Compliant. Pre-scan all modes, worst case please refer to following tables.

802.11 a Chain 0 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10360.00	H	49.25	-50.49	13.48	0.40	-37.41	-30.00	7.41
10360.00	V	49.33	-49.85	13.48	0.40	-36.77	-30.00	6.77
499.60	H	37.71	-72.00	0.00	0.71	-72.71	-54.00	18.71
596.30	V	36.52	-74.37	0.00	0.76	-75.13	-54.00	21.13

802.11 a Chain 0 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10480.00	H	49.62	-50.12	13.32	0.30	-37.10	-30.00	7.10
10480.00	V	48.35	-50.65	13.32	0.30	-37.63	-30.00	7.63
523.40	H	36.85	-72.36	0.00	0.72	-73.08	-54.00	19.08
600.20	V	36.11	-74.71	0.00	0.76	-75.47	-54.00	21.47

802.11 a Chain 1 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10360.00	H	48.33	-51.41	13.48	0.40	-38.33	-30.00	8.33
10360.00	V	49.17	-50.01	13.48	0.40	-36.93	-30.00	6.93
592.70	H	36.28	-71.44	0.00	0.76	-72.20	-54.00	18.20
625.80	V	36.45	-74.03	0.00	0.81	-74.84	-54.00	20.84

802.11 a Chain 1 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10480.00	H	49.32	-50.42	13.32	0.30	-37.40	-30.00	7.40
10480.00	V	48.82	-50.18	13.32	0.30	-37.16	-30.00	7.16
647.50	H	36.57	-70.74	0.00	0.85	-71.59	-54.00	17.59
583.20	V	36.33	-74.81	0.00	0.75	-75.56	-54.00	21.56

802.11 n20 Low channel 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10360.00	H	48.32	-51.42	13.48	0.40	-38.34	-30.00	8.34
10360.00	V	48.14	-51.04	13.48	0.40	-37.96	-30.00	7.96
526.10	H	36.58	-72.57	0.00	0.72	-73.29	-54.00	19.29
657.90	V	35.92	-74.14	0.00	0.86	-75.00	-54.00	21.00

802.11 n20 High channel 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10480.00	H	47.62	-52.12	13.32	0.30	-39.10	-30.00	9.10
10480.00	V	48.12	-50.88	13.32	0.30	-37.86	-30.00	7.86
572.60	H	36.47	-71.68	0.00	0.75	-72.43	-54.00	18.43
682.00	V	36.21	-73.54	0.00	0.91	-74.45	-54.00	20.45

802.11 n40 Low channel 5190 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10380.00	H	48.23	-51.51	13.44	0.38	-38.45	-30.00	8.45
10380.00	V	47.26	-51.89	13.44	0.38	-38.83	-30.00	8.83
629.20	H	36.45	-70.96	0.00	0.81	-71.77	-54.00	17.77
630.50	V	36.88	-73.54	0.00	0.81	-74.35	-54.00	20.35

802.11 n40 High channel 5230 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10460.00	H	48.23	-51.51	13.34	0.31	-38.48	-30.00	8.48
10460.00	V	48.14	-50.89	13.34	0.31	-37.86	-30.00	7.86
591.40	H	36.29	-71.45	0.00	0.76	-72.21	-54.00	18.21
622.80	V	36.17	-74.35	0.00	0.80	-75.15	-54.00	21.15

802.11 ac20 Low channel 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10360.00	H	48.33	-51.41	13.48	0.40	-38.33	-30.00	8.33
10360.00	V	48.15	-51.03	13.48	0.40	-37.95	-30.00	7.95
500.90	H	36.92	-72.77	0.00	0.71	-73.48	-54.00	19.48
647.10	V	36.35	-73.85	0.00	0.84	-74.69	-54.00	20.69

802.11 ac20 High channel 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10480.00	H	48.32	-51.42	13.32	0.30	-38.40	-30.00	8.40
10480.00	V	48.12	-50.88	13.32	0.30	-37.86	-30.00	7.86
544.60	H	36.48	-72.27	0.00	0.73	-73.00	-54.00	19.00
627.40	V	36.09	-74.37	0.00	0.81	-75.18	-54.00	21.18

802.11 ac40 Low channel 5190 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10380.00	H	47.28	-52.46	13.44	0.38	-39.40	-30.00	9.40
10380.00	V	48.13	-51.02	13.44	0.38	-37.96	-30.00	7.96
583.60	H	36.34	-71.57	0.00	0.75	-72.32	-54.00	18.32
649.10	V	36.25	-73.93	0.00	0.85	-74.78	-54.00	20.78

802.11 ac40 High channel 5230 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10460.00	H	48.36	-51.38	13.34	0.31	-38.35	-30.00	8.35
10460.00	V	47.20	-51.83	13.34	0.31	-38.80	-30.00	8.80
628.40	H	36.71	-70.70	0.00	0.81	-71.51	-54.00	17.51
593.70	V	36.48	-74.46	0.00	0.76	-75.22	-54.00	21.22

802.11 ac80 5210 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10420.00	H	48.15	-51.59	13.38	0.35	-38.56	-30.00	8.56
10420.00	V	48.22	-50.87	13.38	0.35	-37.84	-30.00	7.84
592.70	H	36.29	-71.43	0.00	0.76	-72.19	-54.00	18.19
625.80	V	36.33	-74.15	0.00	0.81	-74.96	-54.00	20.96

802.11 ax20 Low channel 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10360.00	H	48.39	-51.35	13.48	0.40	-38.27	-30.00	8.27
10360.00	V	47.10	-52.08	13.48	0.40	-39.00	-30.00	9.00
589.20	H	36.51	-71.28	0.00	0.75	-72.03	-54.00	18.03
633.40	V	36.25	-74.13	0.00	0.82	-74.95	-54.00	20.95

802.11 ax20 High channel 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10480.00	H	48.23	-51.51	13.32	0.30	-38.49	-30.00	8.49
10480.00	V	47.14	-51.86	13.32	0.30	-38.84	-30.00	8.84
625.80	H	36.64	-70.79	0.00	0.81	-71.60	-54.00	17.60
644.70	V	36.27	-73.96	0.00	0.84	-74.80	-54.00	20.80

802.11ax40 Low channel 5190 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10380.00	H	49.32	-50.42	13.44	0.38	-37.36	-30.00	7.36
10380.00	V	48.17	-50.98	13.44	0.38	-37.92	-30.00	7.92
597.10	H	36.42	-71.20	0.00	0.76	-71.96	-54.00	17.96
562.40	V	36.58	-74.96	0.00	0.74	-75.70	-54.00	21.70

802.11ax40 High channel 5230 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10460.00	H	48.66	-51.08	13.34	0.31	-38.05	-30.00	8.05
10460.00	V	48.32	-50.71	13.34	0.31	-37.68	-30.00	7.68
620.50	H	36.79	-70.66	0.00	0.80	-71.46	-54.00	17.46
588.70	V	36.24	-74.80	0.00	0.75	-75.55	-54.00	21.55

802.11 ax80 5210 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
10420.00	H	47.23	-52.51	13.38	0.35	-39.48	-30.00	9.48
10420.00	V	48.29	-50.80	13.38	0.35	-37.77	-30.00	7.77
600.40	H	36.58	-70.98	0.00	0.76	-71.74	-54.00	17.74
593.20	V	36.28	-74.67	0.00	0.76	-75.43	-54.00	21.43

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

5 – TRANSMITTER UNWANTED EMISSIONS WITHIN THE 5 GHZ RLAN BANDS

Definition

Transmitter unwanted emissions within the 5 GHz RLAN bands are radio frequency emissions within the 5 GHz RLAN bands defined in clause 3.1.

Limit




Figure 1: Transmit spectral power mask

Test Procedure


According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.6

Test Data

Test Result: Compliant. Please refer to following Plots:

Chain0-5.2G



802.11 a-5180 MHz



Date: 20.FEB.2023 20:51:21

Date: 20.FEB.2023 20:52:40


802.11 a-5240 MHz



Date: 20.FEB.2023 21:21:36

Date: 20.FEB.2023 21:22:45


802.11 n20-5180 MHz




Date: 20.FEB.2023 20:56:10

Date: 20.FEB.2023 20:57:23

802.11 n20-5240 MHz



Date: 20.FEB.2023 21:16:50




Date: 20.FEB.2023 21:18:01

802.11 n40-5190 MHz




Date: 20.FEB.2023 21:25:56




Date: 20.FEB.2023 21:28:39

802.11 n40-5230 MHz




Date: 20.FEB.2023 21:48:17



Date: 20.FEB.2023 21:50:12



802.11 ac20-5180 MHz



Date: 20.FEB.2023 21:00:29

Date: 20.FEB.2023 21:02:24


802.11 ac20-5240 MHz



Date: 20.FEB.2023 21:11:48

Date: 20.FEB.2023 21:12:58


802.11 ac40-5190 MHz



Date: 20.FEB.2023 21:31:19

Date: 20.FEB.2023 21:32:39


802.11 ac40-5230 MHz



Date: 20.FEB.2023 21:44:45

Date: 20.FEB.2023 21:46:05

802.11 ac80-5210 MHz




Date: 20.FEB.2023 21:56:13



Date: 20.FEB.2023 21:57:37

Chain1-5.2G


802.11 a-5180 MHz





802.11 a-5240 MHz



802.11 n20-5180 MHz



802.11 n20-5240 MHz



Date: 20.FEB.2023 22:58:10

Date: 20.FEB.2023 22:59:25



802.11 n40-5190 MHz



Date: 20.FEB.2023 22:42:15

Date: 20.FEB.2023 22:43:49


802.11 n40-5230 MHz



Date: 20.FEB.2023 22:15:30

Date: 20.FEB.2023 22:16:49


802.11 ac20-5180 MHz




Date: 20.FEB.2023 23:19:44

Date: 20.FEB.2023 23:21:11

802.11 ac20-5240 MHz



Date: 20.FEB.2023 23:04:23




Date: 20.FEB.2023 23:05:56

802.11 ac40-5190 MHz




Date: 20.FEB.2023 22:37:53




Date: 20.FEB.2023 22:39:14

802.11 ac40-5230 MHz




Date: 20.FEB.2023 22:20:27




Date: 20.FEB.2023 22:21:52

802.11 ac80-5210 MHz



Date: 20.FEB.2023 22:10:30




Date: 20.FEB.2023 22:11:51



802.11ax mode

Chain0-5.2G


802.11 ax20-5180 MHz




802.11 ax20-5240 MHz




802.11 ax40-5190 MHz



802.11 ax40-5230 MHz




Date: 20.FEB.2023 21:39:33




Date: 20.FEB.2023 21:40:55

802.11 ax80-5210 MHz



Date: 20.FEB.2023 22:01:50




Date: 20.FEB.2023 22:03:11

Chain1-5.2G

802.11 ax20-5180 MHz




Date: 20.FEB.2023 23:14:41




Date: 20.FEB.2023 23:16:14

802.11 ax20-5240 MHz



Date: 20.FEB.2023 23:10:28




Date: 20.FEB.2023 23:11:41

802.11 ax40-5190 MHz




Date: 20.FEB.2023 22:32:56



Date: 20.FEB.2023 22:34:22

802.11 ax40-5230 MHz



Date: 20.FEB.2023 22:28:05




Date: 20.FEB.2023 22:29:32

802.11 ax80-5210 MHz



Date: 20.FEB.2023 22:06:35



Date: 20.FEB.2023 22:08:07

6 – RECEIVER SPURIOUS EMISSIONS

Definition

Receiver spurious emissions are emissions at any frequency when the equipment is in receive mode.

Limit

The spurious emissions of the receiver shall not exceed the limits given in table 5.

In case of equipment with antenna connectors, these limits apply to emissions at the antenna port (conducted). For emissions radiated by the cabinet or emissions radiated by integral antenna equipment (without antenna connectors), these limits are e.r.p. for emissions up to 1 GHz and e.i.r.p. for emissions above 1 GHz.

Table 5: Spurious radiated emission limits

Frequency range	Maximum power	Measurement bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 26 GHz	-47 dBm	1 MHz

Test Procedure

According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.7

Test Data

Test Result: Compliant. Pre-scan all modes, worst case please refer to following tables.

802.11 a Chain 0 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1580.40	H	50.65	-68.31	9.98	0.81	-59.14	-47.00	12.14
1786.70	V	51.19	-67.19	11.06	0.69	-56.82	-47.00	9.82
93.90	H	40.22	-74.67	0.00	0.32	-74.99	-57.00	17.99
43.30	V	48.22	-48.59	-22.04	0.21	-70.84	-57.00	13.84

802.11 a Chain 0 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1487.63	H	50.12	-69.05	9.44	1.33	-60.94	-47.00	13.94
1591.15	V	50.65	-68.80	10.05	0.74	-59.49	-47.00	12.49
94.50	H	39.83	-74.80	0.00	0.32	-75.12	-57.00	18.12
44.50	V	48.52	-49.76	-20.46	0.21	-70.43	-57.00	13.43

802.11 a Chain 1 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1605.93	H	50.79	-67.96	10.14	0.68	-58.50	-47.00	11.50
1783.93	V	50.92	-67.44	11.05	0.69	-57.08	-47.00	10.08
93.10	H	39.89	-75.34	0.00	0.33	-75.67	-57.00	18.67
44.50	V	48.31	-49.97	-20.46	0.21	-70.64	-57.00	13.64

802.11 a Chain 1 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1578.03	H	50.64	-68.34	9.97	0.83	-59.20	-47.00	12.20
1784.33	V	51.35	-67.01	11.05	0.69	-56.65	-47.00	9.65
94.50	H	40.22	-74.41	0.00	0.32	-74.73	-57.00	17.73
45.10	V	48.54	-50.52	-19.70	0.21	-70.43	-57.00	13.43

802.11 n20 Low channel 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1607.70	H	50.16	-68.57	10.15	0.69	-59.11	-47.00	12.11
1734.40	V	50.29	-67.82	10.90	0.73	-57.65	-47.00	10.65
94.20	H	39.97	-74.79	0.00	0.32	-75.11	-57.00	18.11
43.80	V	48.65	-48.77	-21.38	0.21	-70.36	-57.00	13.36

802.11 n20 High channel 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1105.74	H	50.43	-67.14	7.39	1.02	-60.77	-47.00	13.77
1170.84	V	50.97	-66.99	7.33	1.07	-60.73	-47.00	13.73
94.10	H	41.12	-73.68	0.00	0.32	-74.00	-57.00	17.00
44.70	V	49.65	-48.87	-20.20	0.21	-69.28	-57.00	12.28

802.11 n40 Low channel 5190 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1147.57	H	50.16	-67.08	7.35	1.05	-60.78	-47.00	13.78
1655.57	V	49.94	-68.67	10.49	0.72	-58.90	-47.00	11.90
95.20	H	40.66	-73.68	0.00	0.31	-73.99	-57.00	16.99
44.10	V	48.52	-49.27	-20.99	0.21	-70.47	-57.00	13.47

802.11 n40 High channel 5230 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1560.57	H	50.23	-68.85	9.86	0.94	-59.93	-47.00	12.93
1478.57	V	49.40	-69.77	9.39	1.32	-61.70	-47.00	14.70
93.60	H	41.26	-73.75	0.00	0.32	-74.07	-57.00	17.07
44.50	V	50.03	-48.25	-20.46	0.21	-68.92	-57.00	11.92

802.11 ac20 Low channel 5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1149.62	H	50.83	-66.40	7.35	1.05	-60.10	-47.00	13.10
1252.69	V	51.37	-66.78	7.83	1.14	-60.09	-47.00	13.09
94.10	H	40.97	-73.83	0.00	0.32	-74.15	-57.00	17.15
43.60	V	48.25	-48.93	-21.65	0.21	-70.79	-57.00	13.79

802.11 ac20 High channel 5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1382.37	H	50.83	-66.36	8.88	1.20	-58.68	-47.00	11.68
1450.57	V	51.37	-67.29	9.25	1.28	-59.32	-47.00	12.32
95.20	H	40.61	-73.73	0.00	0.31	-74.04	-57.00	17.04
44.70	V	49.35	-49.17	-20.20	0.21	-69.58	-57.00	12.58

802.11 ac40 Low channel 5190 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1490.04	H	50.50	-68.73	9.45	1.34	-60.62	-47.00	13.62
2416.84	V	50.30	-65.66	12.43	1.28	-54.51	-47.00	7.51
94.30	H	39.98	-74.74	0.00	0.32	-75.06	-57.00	18.06
46.10	V	49.15	-51.57	-18.72	0.21	-70.50	-57.00	13.50

802.11 ac40 High channel 5230 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1558.20	H	50.19	-68.91	9.85	0.96	-60.02	-47.00	13.02
1476.20	V	50.26	-68.87	9.38	1.31	-60.80	-47.00	13.80
96.20	H	40.55	-73.36	0.00	0.30	-73.66	-57.00	16.66
43.70	V	49.36	-47.94	-21.52	0.21	-69.67	-57.00	12.67

802.11 ac80

5210 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1566.71	H	50.83	-68.22	9.90	0.90	-59.22	-47.00	12.22
1631.84	V	50.47	-68.49	10.32	0.70	-58.87	-47.00	11.87
94.60	H	41.22	-73.37	0.00	0.31	-73.68	-57.00	16.68
44.90	V	49.37	-49.40	-19.93	0.21	-69.54	-57.00	12.54

802.11 ax20 Low channel

5180 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1566.78	H	50.34	-68.71	9.90	0.90	-59.71	-47.00	12.71
1631.84	V	50.12	-68.84	10.32	0.70	-59.22	-47.00	12.22
93.90	H	41.08	-73.81	0.00	0.32	-74.13	-57.00	17.13
44.10	V	49.29	-48.50	-20.99	0.21	-69.70	-57.00	12.70

802.11 ax20 High channel

5240 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1529.44	H	49.98	-69.30	9.68	1.15	-60.77	-47.00	13.77
1685.29	V	50.52	-67.64	10.70	0.74	-57.68	-47.00	10.68
93.70	H	40.16	-74.81	0.00	0.32	-75.13	-57.00	18.13
43.50	V	48.73	-48.32	-21.78	0.21	-70.31	-57.00	13.31

802.11ax40 Low channel

5190 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1559.71	H	50.60	-68.49	9.86	0.95	-59.58	-47.00	12.58
1228.34	V	49.77	-68.28	7.58	1.12	-61.82	-47.00	14.82
94.50	H	40.26	-74.37	0.00	0.32	-74.69	-57.00	17.69
46.10	V	49.68	-51.04	-18.72	0.21	-69.97	-57.00	12.97

802.11ax40 High channel

5230 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1580.66	H	49.81	-69.15	9.98	0.81	-59.98	-47.00	12.98
1786.96	V	49.83	-68.55	11.06	0.69	-58.18	-47.00	11.18
95.20	H	40.36	-73.98	0.00	0.31	-74.29	-57.00	17.29
44.80	V	49.10	-49.55	-20.06	0.21	-69.82	-57.00	12.82

802.11 ax80

5210 MHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1108.37	H	49.92	-67.63	7.39	1.03	-61.27	-47.00	14.27
1173.47	V	49.09	-68.87	7.33	1.07	-62.61	-47.00	15.61
96.20	H	40.28	-73.63	0.00	0.30	-73.93	-57.00	16.93
44.20	V	49.03	-48.88	-20.86	0.21	-69.95	-57.00	12.95

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit - Absolute Level

8 – ADAPTIVITY

Applicable Standard

Adaptivity (Channel Access Mechanism) is an automatic mechanism by which a device limits its transmissions and gains access to an Operating Channel.

§4.2.7.3.1 Frame Based Equipment:

Frame Based Equipment shall implement a Listen Before Talk (LBT) based Channel Access Mechanism to detect the presence of other RLAN transmissions on an Operating Channel.

§4.2.7.3.2 Load Based Equipment:

Load based Equipment shall implement a Listen Before Talk (LBT) based Channel Access Mechanism to detect the presence of other RLAN transmissions on an Operating Channel.


Limit

According to ETSI EN 301 893 V2.1.1 (2017-05) §4.2.7.3.1&§4.2.7.3.2

Test Procedure

According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.9

Block Diagram of Test Setup




Test Data




Test Result: Compliant. Please refer to following tables.



Test Mode	Channel	Priority Class	Max. COT [ms]	Limit [ms]	Min.Idle Time[ms]	Limit [ms]	Idle Period probability	Verdict
802.11a	5180	4	0.313	4.000	0.061	0.027	See the graph	PASS
802.11n40	5190	4	1.405	4.000	0.032	0.027	See the graph	PASS



Test Mode	Channel	Interference Type	Add interference Time[ms]	Max.Short Control number[n]	Limit [n]	Max.Short Control Time[ms]	Limit [ms]	Verdict
802.11a	5180	AWGN	2100	1	50	0.6	2.5	PASS
		OFDM	2100	1	50	1.7	2.5	PASS
		LTE	2100	1	50	2.3	2.5	PASS
802.11n40	5190	AWGN	2100	1	50	2.4	2.5	PASS



Please refer to following plots:















9 – RECEIVER BLOCKING

Applicable Standard

Receiver blocking is a measure of the capability of the equipment to receive a wanted signal on its operating channel without exceeding a given degradation due to the presence of an unwanted input signal (blocking signal) on frequencies other than those of the operating bands provided in table 1.

Limit

The minimum performance criterion shall be a PER of less than or equal to 10 %. The manufacturer may declare alternative performance criteria as long as that is appropriate for the intended use of the equipment

While maintaining the minimum performance criteria as defined in clause 4.2.8.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined in table 9.

Table 9: Receiver Blocking parameters

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)		Type of blocking signal
		Master or Slave with radar detection (see table D.2, note 2)	Slave without radar detection (see table D.2, note 2)	
$P_{min} + 6$ dB	5 100	-53	-59	Continuous Wave
$P_{min} + 6$ dB	4 900 5 000 5 975	-47	-53	Continuous Wave

NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined clause 4.2.8.3 in the absence of any blocking signal.
 NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the same levels should be used at the antenna connector irrespective of antenna gain.

Test Procedure

According to ETSI EN 301 893 V2.1.1 (2017-05) §5.4.10

Block Diagram of Test Setup




Figure 14: Test Set-up for receiver blocking

Test Data

Test Result: *Compliant. Please refer to following tables.*

Note: CMW500 was used to monitor the PER, and the worst case as below.

Test Mode	Pmin (dBm)	Wanted signal Power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm)	Max Blocking Signal Power (dBm)	PER (%)	Limit (%)
802.11 a (5180 MHz)	-92	-86	5100	-53	-46	5.1	≤ 10
			4900	-47	-39	4.3	
			5000	-47	-41	3.2	
			5975	-47	-40	2.9	

EXHIBIT A – EUT PHOTOGRAPHS


For photos in this section, please refer to report No.: DG2230214-06388E-02 EXHIBIT A..

EXHIBIT B – TEST SET UP PHOTOGRAPHS

Radiated Emission Below 1GHz View



Radiated Emission Above 1GHz View



*******END OF REPORT*******