


## TEST REPORT

Applicant	SHENZHEN TENDA TECHNOLOGY CO.,LTD.
Address	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

Manufacturer or Supplier	SHENZHEN TENDA TECHNOLOGY CO.,LTD.	
Address	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052	
Product	300Mbps Wireless N Access Point	
Brand Name	Tenda	
Model	AP4	
Additional Model & Model Difference	N/A	
Date of tests	May 14, 2015 ~ May 29, 2015 Nov. 30, 2016 ~ Dec. 02, 2016 Jun. 23, 2017 ~ Jul. 08, 2017	


The submitted sample of the above equipment has been tested according to the requirements of the following standards:

☒ **EN 300 328 V2.1.1 (2016-11)**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Tom Chen  
Project Engineer / EMC Department

Approved by Glyn He  
Supervisor / EMC Department




Date: Aug. 02, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>4</b>
<b>1. SUMMARY OF TEST RESULTS .....</b>	<b>5</b>
1.1. TEST INSTRUMENTS .....	6
1.2. MEASUREMENT UNCERTAINTY .....	7
1.3. MAXIMUM MEASUREMENT UNCERTAINTY .....	7
<b>2. GENERAL INFORMATION.....</b>	<b>8</b>
2.1. GENERAL DESCRIPTION OF EUT .....	8
2.2. DESCRIPTION OF TEST MODES .....	9
2.2.1. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
2.3. GENERAL DESCRIPTION OF APPLIED STANDARDS.....	14
2.4. DESCRIPTION OF SUPPORT UNITS .....	14
<b>3 TEST PROCEDURES AND RESULTS .....</b>	<b>15</b>
<b>TRANSMITTER PARAMETERS.....</b>	<b>15</b>
3.1. RF OUTPUT POWER.....	15
3.1.1. LIMITS OF RF OUTPUT POWER .....	15
3.1.2. TEST PROCEDURE .....	15
3.1.3. DEVIATION FROM TEST STANDARD .....	15
3.1.4. TEST SETUP .....	15
3.1.5. TEST RESULTS .....	16
3.2. POWER SPECTRAL DENSITY.....	17
3.2.1. LIMIT OF POWER SPECTRAL DENSITY .....	17
3.2.2. TEST PROCEDURE .....	17
3.2.3. DEVIATION FROM TEST STANDARD .....	17
3.2.4. TEST SETUP .....	17
3.2.5. TEST RESULTS .....	18
3.3. OCCUPIED CHANNEL BANDWIDTH .....	19
3.3.1. LIMIT OF OCCUPIED CHANNEL BANDWIDTH.....	19
3.3.2. TEST PROCEDURE .....	19
3.3.3. DEVIATION FROM TEST STANDARD .....	19
3.3.4. TEST SETUP .....	19
3.3.5. TEST RESULTS .....	20
3.4. TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN .....	21
3.4.1. LIMITS OF TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN.....	21
3.4.2. TEST PROCEDURE .....	21
3.4.3. DEVIATION FROM TEST STANDARD .....	21
3.4.4. TEST SETUP .....	22
3.4.5. TEST RESULTS .....	22
3.5. ADAPTIVE (CHANNEL ACCESS MECHANISM) .....	24
3.5.1. APPLICABILITY OF ADAPTIVE REQUIREMENTS AND LIMIT FOR WIDE BAND MODULATION TECHNIQUES.....	24
3.5.2. TEST PROCEDURES .....	25
3.5.3. TEST SETUP CONFIGURATION.....	25
3.5.4. INTERFERENCE THRESHOLD LEVEL .....	26
3.5.5. LIST OF MEASUREMENTS.....	27
3.5.6. TEST RESULT .....	28
3.5.6.1. ADAPTIVE RESULT.....	28
3.5.6.2. THE CHANNEL OCCUPANCY TIME RESULT.....	33



3.5.6.3.	SHORT CONTROL SIGNALLING TRANSMISSIONS RESULT .....	36
3.6.	TRANSMITTER SPURIOUS EMISSIONS .....	37
3.6.1.	LIMITS OF TRANSMITTER SPURIOUS EMISSIONS .....	37
3.6.2.	TEST PROCEDURE .....	37
3.6.3.	DEVIATION FROM TEST STANDARD .....	38
3.6.4.	TEST SETUP .....	38
3.6.5.	TEST RESULTS .....	39
	<b>RECEIVER PARAMETERS .....</b>	<b>43</b>
3.7.	RECEIVER SPURIOUS RADIATION .....	43
3.7.1.	LIMITS OF RECEIVER SPURIOUS RADIATION .....	43
3.7.2.	TEST PROCEDURE .....	43
3.7.3.	DEVIATION FROM TEST STANDARD .....	43
3.7.4.	TEST SETUP .....	43
3.7.5.	TEST RESULTS .....	44
3.8.	RECEIVER BLOCKING .....	47
3.8.1.	LIMITS OF RECEIVER BLOCKING .....	47
3.8.2.	TEST PROCEDURE .....	48
3.8.3.	DEVIATION FROM TEST STANDARD .....	48
3.8.4.	TEST SETUP CONFIGURATION .....	49
3.8.5.	TEST RESULT .....	50
<b>4</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>	<b>51</b>
<b>5</b>	<b>APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....</b>	<b>54</b>

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RE150514N006	Original release	Jun. 02, 2015
RE161128N061	Based on the original report RE150514N006 renewed EN300328 1.8.1 to 1.9.1 and it need to be retested ROP/PSD/AD/OCB/OOB test items after engineer evaluated.	Dec. 21, 2016
RE170623N070	Based on the report RE161128N061 renewed standard and RED directive. It needs to retest receiver blocking test item.	Aug. 02, 2017

## 1. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

EN 300 328 V2.1.1		
Clause	Test Parameter	Results
	<b>TRANSMITTER PARAMETERS</b>	
4.3.2.2	RF Output Power	Pass
4.3.2.3	Power Spectral Density	Pass
4.3.2.6	Adaptivity	Pass (Note 1)
4.3.2.7	Occupied Channel Bandwidth	Pass
4.3.2.8	Transmitter unwanted emission in the OOB domain	Pass
4.3.2.9	Transmitter unwanted emissions in the spurious domain	Pass
4.3.2.12	Geo-location capability	Not Applicable
	<b>RECEIVER PARAMETERS</b>	
4.3.2.10	Receiver Spurious Emissions	Pass
4.3.2.11	Receiver Blocking	Pass

Note: 1. These requirements do not apply for equipment with a maximum declared RF Output power of less than 10 dBm EIRP or for equipment when operating in a mode where the RF Output power is less than 10 dBm EIRP.

**1.1. TEST INSTRUMENTS**

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 11,17	Mar. 10,18
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Apr. 05,17	Apr. 04,18
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Horn Antenna	ETS-Lindgren	3117	00062558	Jul. 02,17	Jul. 01,18
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 16	Aug. 07, 17
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 06,17	Mar. 05,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Mar. 15,17	Mar. 14,18
Amplifier	Burgeon	BPA-530	100220	Apr. 05,17	Apr. 04,18
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Mar. 06,17	Mar. 05,18
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,16	Nov. 03,17
Power Sensor	Keysight	U2021XA	MY55060016	May 19,17	May 18,18
Power Sensor	Keysight	U2021XA	MY55060018	May 19,17	May 18,18
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 13, 16	Oct.12, 17
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 04,16	Nov. 03,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Spectrum Analyzer	Keysight	N9020A	MY55400499	Apr. 05,17	Apr. 04,18
Signal Generator	Agilent	N5183A	MY50140980	Nov. 04,16	Nov. 03,17
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Dec.05, 16	Dec. 04, 17
Wireless Connectivity Tester	Rohde&Schwarz	CMW270	100908	Jan. 09, 17	Jan. 08, 18
Vector Signal Generator	Rohde&Schwarz	SMBV100A	257199	Apr. 18, 17	Apr. 17, 18
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A

**NOTE:**

1. The test was performed in 966 Chamber and RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRG/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

## 1.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 1.132 \times 10^{-4} \%$
RF output power, conducted	$\pm 1.017 \text{ dB}$
Power Spectral Density, conducted	$\pm 1.017 \text{ dB}$
Unwanted Emissions, conducted	$\pm 2.855 \text{ dB}$
All emissions, radiated	$\pm 2.855 \text{ dB}$
Temperature	$\pm 0.7^\circ \text{C}$
Supply voltages	$\pm 0.04 \%$
Time	$\pm 4 \%$

## 1.3. MAXIMUM MEASUREMENT UNCERTAINTY

For the test methods, according to ETSI EN 300 328 standard, the measurement uncertainty figures shall be calculated in accordance with ETR 100 028-1 [4] and shall correspond to an expansion factor (coverage factor)  $k = 1,96$  or  $k = 2$  (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

### Maximum measurement uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 5 \%$
RF output power, conducted	$\pm 1,5 \text{ dB}$
Power Spectral Density, conducted	$\pm 3 \text{ dB}$
Unwanted Emissions, conducted	$\pm 3 \text{ dB}$
All emissions, radiated	$\pm 6 \text{ dB}$
Temperature	$\pm 3^\circ \text{C}$
Supply voltages	$\pm 3 \%$
Time	$\pm 5 \%$

## 2. GENERAL INFORMATION

### 2.1. GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	300Mbps Wireless N Access Point
<b>TEST MODEL</b>	AP4
<b>NOMINAL VOLTAGE</b>	DC 9V From Adapter
<b>OPERATING TEMPERATURE RANGE</b>	-10 ~ +45°C
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>OPERATING FREQUENCY</b>	2412-2472MHz for 11b/g/n(HT20) 2422-2462MHz for 11n(HT40)
<b>ADPTIVE/NON-ADPTIVE</b>	<input type="checkbox"/> non-adaptive Equipment <input checked="" type="checkbox"/> adaptive Equipment without the possibility to switch to a non-adaptive mode <input type="checkbox"/> adaptive Equipment which can also operate in a non-adaptive mode
<b>EIRP POWER (MAX.)</b>	19.06dBm (Measured Max.)
<b>ANTENNA TYPE</b>	Dipole Antenna; 5.0dBi gain
<b>CABLE SUPPLIED</b>	RJ45 Cable: Unshielded, Detachable, 1.0m

Note:

- The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.
- For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- Please refer to the EUT photo document (Reference No.: 170623N070) for detailed product photo.
- The EUT can be powered by adapter as list as attach.

<b>ADAPTER</b>	
<b>BRAND:</b>	N/A
<b>MODEL:</b>	TEA09E-09060
<b>INPUT:</b>	AC 100-240V, 50/60Hz, 0.3A
<b>OUTPUT:</b>	DC 9V/0.6A
<b>DC LINE:</b>	Unshielded, Non-detachable, 1.5m

- The EUT have MIMO function, provides 2 completed transmitters and 2 receivers.

<b>MODULATION MODE</b>	<b>TX FUNCTION</b>
<b>802.11b</b>	1TX/1RX
<b>802.11g</b>	1TX/1RX
<b>802.11n (HT20)</b>	2TX/2RX
<b>802.11n (HT40)</b>	2TX/2RX



## 2.2. DESCRIPTION OF TEST MODES

13 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	8	2447 MHz
2	2417 MHz	9	2452 MHz
3	2422 MHz	10	2457 MHz
4	2427 MHz	11	2462 MHz
5	2432 MHz	12	2467 MHz
6	2437 MHz	13	2472 MHz
7	2442 MHz		

9 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	8	2447 MHz
4	2427 MHz	9	2452 MHz
5	2432 MHz	10	2457 MHz
6	2437 MHz	11	2462 MHz
7	2442 MHz		

## 2.2.1. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO								DESCRIPTION
	ROP	PSD	AD	OCB	OOB	SE<1G	SE≥1G	RB	
A	√	√	√	√	√	√	√	√	Powered by Adapter with WIFI link

Where **ROP**: RF Output Power **PSD**: Power Spectral Density  
**AD**: Adaptivity (Channel Access Mechanism) **OCB**: Occupied Channel Bandwidth  
**OOB**: Transmitter unwanted emission in the **SE<1G**: Spurious Emissions below 1GHz out-of-band domain  
**SE≥1G**: Spurious Emissions above 1GHz **RB**: Receiver Blocking

### **RF OUTPUT POWER TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1, 7, 13	DSSS	DBPSK	1.0
802.11g	1 to 13	1, 7, 13	OFDM	BPSK	6.0
802.11n (20M)	1 to 13	1, 7, 13	OFDM	BPSK	6.5
802.11n (40M)	3 to 11	3, 7, 11	OFDM	BPSK	13.5

### **POWER SPECTRAL DENSITY TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1, 7, 13	DSSS	DBPSK	1.0
802.11g	1 to 13	1, 7, 13	OFDM	BPSK	6.0
802.11n (20M)	1 to 13	1, 7, 13	OFDM	BPSK	6.5
802.11n (40M)	3 to 11	3, 7, 11	OFDM	BPSK	13.5

**ADAPTIVITY TEST:**

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY
802.11b	1 to 13	1, 13	DSSS
802.11g	1 to 13	1, 13	OFDM
802.11n (20M)	1 to 13	1, 13	OFDM
802.11n (40M)	3 to 11	3, 11	OFDM

**OCCUPIED CHANNEL BANDWIDTH TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1, 13	DSSS	DBPSK	1.0
802.11g	1 to 13	1, 13	OFDM	BPSK	6.0
802.11n (20M)	1 to 13	1, 13	OFDM	BPSK	6.5
802.11n (40M)	3 to 11	3, 11	OFDM	BPSK	13.5

**TRANSMITTER UNWANTED EMISSION IN THE OUT-OF-BAND DOMAIN TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1, 7, 13	DSSS	DBPSK	1.0
802.11g	1 to 13	1, 7, 13	OFDM	BPSK	6.0
802.11n (20M)	1 to 13	1, 7, 13	OFDM	BPSK	6.5
802.11n (40M)	3 to 11	3, 7, 11	OFDM	BPSK	13.5

**SPURIOUS EMISSIONS TEST (BELOW 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1	DSSS	DBPSK	1
Receiver	1 to 13	1	-	-	-

**SPURIOUS EMISSIONS TEST (ABOVE 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1, 13	DSSS	DBPSK	1.0
802.11g	1 to 13	1, 13	OFDM	BPSK	6.0
802.11n (20M)	1 to 13	1, 13	OFDM	BPSK	6.5
802.11n (40M)	3 to 11	3, 11	OFDM	BPSK	13.5
Receiver	1 to 13	1, 13	-	-	-

**RECEIVER BLOCKING TEST:**

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 13	1, 13	DSSS	DBPSK	1.0



**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ROP	25deg. C, 60%RH	DC 9V from adapter	Robert Cheng
PSD	25deg. C, 60%RH	DC 9V from adapter	Robert Cheng
AD	25deg. C, 60%RH	DC 9V from adapter	Robert Cheng
OCB	25deg. C, 60%RH	DC 9V from adapter	Robert Cheng
OOB	25deg. C, 60%RH	DC 9V from adapter	Robert Cheng
SE<1G	25deg. C, 55%RH	DC 9V from adapter	Bob Chen
SE≥1G	25deg. C, 55%RH	DC 9V from adapter	Bob Chen
RB	25deg. C, 60%RH	DC 9V from adapter	Robert Cheng

### 2.3. GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

#### **EN 300 328 V2.1.1 (2016-11)**

All test items have been performed and recorded as per the above standards.

### 2.4. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without any other necessary accessories or support units.

### 3 TEST PROCEDURES AND RESULTS

#### TRANSMITTER PARAMETERS

##### 3.1. RF OUTPUT POWER

###### 3.1.1. LIMITS OF RF OUTPUT POWER

CONDITION	FREQUENCY BAND	LIMIT (e.i.r.p.)
Under all test conditions	2400 ~ 2483.5 MHz	AV: 20dBm

###### 3.1.2. TEST PROCEDURE

Refer to chapter 5.4.2.2 of ETSI EN 300 328 V2.1.1.

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

###### 3.1.3. DEVIATION FROM TEST STANDARD

No deviation.

###### 3.1.4. TEST SETUP

The measurement was performed at both normal environmental conditions and at the extremes of the operating temperature. The measurement was performed at the lowest, the middle, and the highest channel. The equipment was configured to operate under its worst case situation with respect to output power. (In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator.) Controlling software has been activated to set the EUT on specific channel and power level.



## 3.1.5. TEST RESULTS

TEST CONDITION			EIRP POWER (dBm)		
			(CH1) 2412 MHz	(CH7) 2442 MHz	(CH13) 2472 MHz
802.11b					
T <sub>nom</sub> (°C)	+25	V <sub>nom</sub> (v)	17.87	18.01	17.94
T <sub>min</sub> (°C)	-10		18.24	18.19	18.29
T <sub>max</sub> (°C)	+45		17.61	17.68	17.49
802.11g					
T <sub>nom</sub> (°C)	+25	V <sub>nom</sub> (v)	17.41	17.69	17.28
T <sub>min</sub> (°C)	-10		17.86	17.91	17.52
T <sub>max</sub> (°C)	+45		17.16	17.19	16.74
802.11n (20M)					
T <sub>nom</sub> (°C)	+25	V <sub>nom</sub> (v)	18.72	18.62	18.74
T <sub>min</sub> (°C)	-10		18.95	19.06	19.04
T <sub>max</sub> (°C)	+45		18.36	18.37	18.55
TEST CONDITION			EIRP POWER (dBm)		
			(CH3) 2422 MHz	(CH7) 2442 MHz	(CH11) 2462 MHz
802.11n (40M)					
T <sub>nom</sub> (°C)	+25	V <sub>nom</sub> (v)	17.76	17.69	17.75
T <sub>min</sub> (°C)	-10		18.16	18.11	18.16
T <sub>max</sub> (°C)	+45		17.41	17.19	17.31

**NOTE:** 1.EIRP = Conducted output power + ANT Gain



## 3.2. POWER SPECTRAL DENSITY

### 3.2.1. LIMIT OF POWER SPECTRAL DENSITY

CONDITION	FREQUENCY BAND	LIMIT (e.i.r.p.)
Under normal conditions	2400 ~ 2483.5 MHz	10dBm / 1MHz

### 3.2.2. TEST PROCEDURE

Refer to chapter 5.4.3.2 of ETSI EN 300 328 V2.1.1.

Measurement Method	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement
<input checked="" type="checkbox"/> Option 1: For equipment with continuous and non-continuous transmissions	
<input type="checkbox"/> Option 2: For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle (e.g. Frame Based equipment)	

### 3.2.3. DEVIATION FROM TEST STANDARD

No deviation.

### 3.2.4. TEST SETUP

The measurement was performed at normal environmental conditions only. The measurement was performed at the lowest, the middle, and the highest channel. The equipment was configured to operate under its worst case situation with respect to output power. (In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator.) Controlling software has been activated to set the EUT on specific status.

### 3.2.5. TEST RESULTS

#### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER DENSITY (dBm/1MHz) (E.I.R.P)	LIMIT (dBm/1MHz) (E.I.R.P)	PASS/FAIL
1	2412.00	9.86	10	PASS
7	2442.00	<b>9.94</b>	10	PASS
13	2472.00	9.92	10	PASS

#### 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER DENSITY (dBm/1MHz) (E.I.R.P)	LIMIT (dBm/1MHz) (E.I.R.P)	PASS/FAIL
1	2412.00	7.22	10	PASS
7	2442.00	7.52	10	PASS
13	2472.00	7.07	10	PASS

#### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER DENSITY (dBm/1MHz) (E.I.R.P)	LIMIT (dBm/1MHz) (E.I.R.P)	PASS/FAIL
1	2412.00	8.33	10	PASS
7	2442.00	8.23	10	PASS
13	2472.00	8.34	10	PASS

#### 802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER DENSITY (dBm/1MHz) (E.I.R.P)	LIMIT (dBm/1MHz) (E.I.R.P)	PASS/FAIL
3	2422.00	3.68	10	PASS
7	2442.00	3.58	10	PASS
11	2462.00	3.65	10	PASS

### 3.3. OCCUPIED CHANNEL BANDWIDTH

#### 3.3.1. LIMIT OF OCCUPIED CHANNEL BANDWIDTH

CONDITION		LIMIT
All types of equipment		Shall fall completely within the band 2400 to 2483.5 MHz.
Additional requirement	For non-adaptive using wide band modulations other than FHSS system and e.i.r.p >10dBm.	Less than 20MHz
	For non-adaptive Frequency Hopping system and e.i.r.p >10dBm.	Less than 5MHz

#### 3.3.2. TEST PROCEDURE

Refer to chapter 5.4.7.2 of ETSI EN 300 328 V2.1.1.

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

#### 3.3.3. DEVIATION FROM TEST STANDARD

No deviation.

#### 3.3.4. TEST SETUP

The measurement was performed at normal environmental conditions only. This measurement was performed at the lowest and the highest channel. The equipment was configured to operate under its worst case situation with respect to output power. (In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator.) Controlling software has been activated to set the EUT on specific status.

### 3.3.5. TEST RESULTS

#### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	OCCUPIED BANDWIDTH (MHz)	Measured frequencies		LIMIT	PASS/FAIL
			FL (MHz)	FH (MHz)		
1	2412	10.56	2406.64	2417.20	FL > 2400 MHz and FH < 2483.5 MHz	PASS
13	2472	10.56	2466.64	2477.20		PASS

#### 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	OCCUPIED BANDWIDTH (MHz)	Measured frequencies		LIMIT	PASS/FAIL
			FL (MHz)	FH (MHz)		
1	2412	16.72	2403.60	2420.32	FL > 2400 MHz and FH < 2483.5 MHz	PASS
13	2472	16.72	2463.60	2480.32		PASS

#### 802.11n(20M)

CHANNEL	CHANNEL FREQUENCY (MHz)	OCCUPIED BANDWIDTH (MHz)	Measured frequencies		LIMIT	PASS/FAIL
			FL (MHz)	FH (MHz)		
1	2412	17.84	2403.04	2420.88	FL > 2400 MHz and FH < 2483.5 MHz	PASS
13	2472	17.84	2463.04	2480.88		PASS

#### 802.11n(40M)

CHANNEL	CHANNEL FREQUENCY (MHz)	OCCUPIED BANDWIDTH (MHz)	Measured frequencies		LIMIT	PASS/FAIL
			FL (MHz)	FH (MHz)		
3	2422	36.64	2403.60	2440.24	FL > 2400 MHz and FH < 2483.5 MHz	PASS
11	2462	36.64	2443.60	2480.24		PASS


Note: FL is the lowest frequency of the 99% occupied bandwidth of power envelope.  
FH is the highest frequency of the 99% occupied bandwidth of power envelope.



### 3.4. TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

#### 3.4.1. LIMITS OF TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

CONDITION	LIMIT
Under all test conditions	The transmitter unwanted emissions in the out-of-band domain but outside the allocated band, shall not exceed the values provided by the mask in below figure.



#### 3.4.2. TEST PROCEDURE

Refer to chapter 5.4.8.2 of ETSI EN 300 328 V2.1.1.

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

#### 3.4.3. DEVIATION FROM TEST STANDARD

No deviation.

### 3.4.4. TEST SETUP

The measurement was performed at normal environmental conditions only. This measurement was performed at the lowest and the highest channel. The equipment was configured to operate under its worst case situation with respect to output power. (In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator.) The frequency has to be recorded for the right and left end above threshold of highest and lowest channel respectively.

### 3.4.5. TEST RESULTS

#### 802.11b

CHANNEL FREQ.(MHz)			2412				2472			
TEST CONDITION			OOB Emission (MHz)				OOB Emission (MHz)			
			2389.44 ~ 2400		2378.88 ~ 2389.44		2483.5 ~ 2494.06		2494.06 ~ 2504.62	
Temperature		Voltage	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)
Tnorm(°C)	25	Normal	2399.50	-42.44	2388.94	-52.87	2485.00	-41.83	2494.56	-52.54
Limit (dBm/MHz)			-10.00		-20.00		-10.00		-20.00	
PASS/FAIL			PASS		PASS		PASS		PASS	

#### 802.11g

CHANNEL FREQ.(MHz)			2412				2472			
TEST CONDITION			OOB Emission (MHz)				OOB Emission (MHz)			
			2383.28 ~ 2400		2366.56 ~ 2383.28		2483.5 ~ 2500.22		2500.22 ~ 2516.94	
Temperature		Voltage	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)
Tnorm(°C)	25	Normal	2398.50	-40.40	2379.78	-51.84	2487.00	-35.91	2503.72	-54.27
Limit (dBm/MHz)			-10.00		-20.00		-10.00		-20.00	
PASS/FAIL			PASS		PASS		PASS		PASS	

802.11n (20M)

CHANNEL FREQ.(MHz)			2412				2472			
TEST CONDITION			OOB Emission (MHz)				OOB Emission (MHz)			
			2382.16 ~ 2400		2364.32 ~ 2382.16		2483.5 ~ 2501.34		2501.34 ~ 2519.18	
Temperature		Voltage	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)
Tnorm(°C)	25	Normal	2399.50	-38.39	2381.66	-50.91	2486.00	-36.55	2502.84	-51.62
Limit (dBm/MHz)			-10.00		-20.00		-10.00		-20.00	
PASS/FAIL			PASS		PASS		PASS		PASS	

802.11n (40M)

CHANNEL FREQ.(MHz)			2422				2462			
TEST CONDITION			OOB Emission (MHz)				OOB Emission (MHz)			
			2363.36 ~ 2400		2326.72 ~ 2363.36		2483.5 ~ 2520.14		2520.14 ~ 2556.78	
Temperature		Voltage	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)	Freq. (MHz)	Power (dBm)
Tnorm(°C)	25	Normal	2399.50	-29.65	2361.86	-51.54	2484.00	-31.27	2521.64	-53.64
Limit (dBm/MHz)			-10.00		-20.00		-10.00		-20.00	
PASS/FAIL			PASS		PASS		PASS		PASS	

**3.5. ADAPTIVE (CHANNEL ACCESS MECHANISM)****3.5.1. APPLICABILITY OF ADAPTIVE REQUIREMENTS AND LIMIT FOR WIDE BAND MODULATION TECHNIQUES**

Requirement	Operational Mode			
	Non-LBT based Detect and Avoid	LBT based Detect and Avoid		
		Frame Based Equipment	Load Based Equipment (CCA using 'energy detect')	Load Based Equipment (CCA not using any of the mechanisms referenced as note 2)
Minimum Clear Channel Assessment (CCA) Time	NA	18 us (see note 1)	(see note 2)	18 us (see note 1)
Maximum Channel Occupancy (COT) Time	40 ms	1 ms to 10 ms	(see note 2)	13 ms
Minimum Idle Period	5us	5% of COT	(see note 2)	18us (see note 3)
Extended CCA check	NA	NA	(see note 2)	18us~160us
Short Control Signalling Transmissions	Maximum duty cycle of 10 % within an observation period of 50 ms (see note 4)			
NOTE 1: The CCA time used by the equipment shall be declared by the supplier.				
NOTE 2: Load Based Equipment may implement an LBT based spectrum sharing mechanism based on the Clear Channel Assessment (CCA) mode using energy detect, as described in IEEE 802.11™-2012 clause 9, clause 10, clause 16, clause 17, clause 19 and clause 20, or in IEEE 802.15.4™-2011 [i.4], clause 4, clause 5 and clause 8				
NOTE 3: The Idle Period in between transmissions is considered to be the CCA or the Extended CCA check as there are no transmissions during this period.				
NOTE 4: Adaptive equipment may or may not have Short Control Signalling Transmissions				

**Interference threshold level**

Maximum transmit power ( $P_H$ ) EIRP dBm	Threshold level (TL) (see notes 1 and 2)
20	-70 dBm / MHz
NOTE 1: For a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G)	
NOTE 2: For power levels less than 20 dBm e.i.r.p. the CCA threshold level may be relaxed to: $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW} / P_{out})$ ; ( $P_{out}$ in mW e.i.r.p.)	

Wanted signal mean power from companion device	Unwanted signal frequency (MHz)	Unwanted signal power (dBm)
sufficient to maintain the link (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 3)
NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.		
NOTE 2: A typical value which can be used in most cases is -50 dBm/MHz.		
NOTE 3: The level specified is the level in front of the UUT antenna. In case of conducted measurements, this level has to be corrected by the actual antenna assembly gain.		




### 3.5.2. TEST PROCEDURES

Refer to chapter 5.4.6.2 of ETSI EN 300 328 V2.1.1.

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

### 3.5.3. TEST SETUP CONFIGURATION



### 3.5.4. INTERFERENCE THRESHOLD LEVEL

#### Detection Threshold Level

The maximum EIRP power is 19.06dBm and antenna gain is 5dBi.  
 Detection Threshold level=  $-70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW} / (19.06\text{dBm})+5)$   
 =  $-64.06\text{dBm/MHz}$ , The interference signal level to the UUT is  $-64.06\text{dBm/MHz}$



**3.5.5. LIST OF MEASUREMENTS**

UUT Operational Mode	Applicable	Limit	
		The Maximum Channel Occupancy Time	The Minimum idle Period
Frame Based Equipment		meet in 1ms ~ 10ms	>5% x channel occupancy time
Load Based Equipment (Base on 'Spectrum Sharing' mechanisms)		Follow IEEE 802.11 Less than _____ms	Follow IEEE 802.11 More than _____ms
Load Based Equipment (Not using any of the mechanisms referenced)	v	13ms	18us

Clause	Test Parameter	Remarks	Pass/Fail
4.3.2.6.3.2.2	Adaptive (Frame Based Equipment)	Not Applicable	NA
4.3.2.6.3.2.3	Adaptive (Load Based Equipment)	Applicable	Pass
4.3.2.6.4	Short Control Signalling Transmissions	Applicable	Pass




### 3.5.6. TEST RESULT

#### 3.5.6.1. ADAPTIVE RESULT

##### OPERATING FREQUENCY BANDS AND MODE OF EUT


Operational Mode	Operating Frequency - Low Channel (MHz)	Operating Frequency -High Channel (MHz)	Test Result
802.11b	2412	2472	PASS
802.11g	2412	2472	PASS
802.11n 20M	2412	2472	PASS
802.11n 40M	2422	2462	PASS

802.11b  
2412MHz




Adaptive Result

2472MHz




Adaptive Result

802.11g  
2412MHz




Adaptive Result

2472MHz




Adaptive Result

802.11n 20M  
2412MHz




Adaptive Result

2472MHz




Adaptive Result

802.11n 40M  
2422MHz



Adaptive Result

2462MHz



Adaptive Result



### 3.5.6.2. THE CHANNEL OCCUPANCY TIME RESULT


#### OPERATING FREQUENCY BANDS AND MODE OF EUT

Operational Mode	Operating Frequency Low Channel (MHz)	The Channel Occupancy Time (ms)	Minimum Idle Period (ms)	Test Result
802.11b	2412	1.310	0.137 (NOTE )	Meeting IEEE 802.11-2012 Requirements
802.11g	2412	0.280	0.064 (NOTE )	Meeting IEEE 802.11-2012 Requirements
802.11n (HT20)	2412	3.000	0.067 (NOTE )	Meeting IEEE 802.11-2012 Requirements
802.11n (HT40)	2422	1.321	0.067 (NOTE )	Meeting IEEE 802.11-2012 Requirements


#### **NOTE : MINIMUM CLEAR CHANNEL ASSESSMENT (CCA) TIME**

The Idle Period in between transmissions is considered to be the CCA or the Extended CCA check as there are no transmissions during this period.( Clause 4.3.2.6.3.2.3 NOTE 1)

## 802.11b




## 802.11g mode






**Test Report No.: RE170623N070**

### 802.11n(HT20) mode



### 802.11n(HT40) mode





### 3.5.6.3. SHORT CONTROL SIGNALLING TRANSMISSIONS RESULT

#### 802.11b

SHORT CONTROL SIGNALLING TRANSMISSION RESULT
The SCST Duty cycle = No short control signalling

#### 802.11g

SHORT CONTROL SIGNALLING TRANSMISSION RESULT
The SCST Duty cycle = No short control signalling

#### 802.11n 20MHz

SHORT CONTROL SIGNALLING TRANSMISSION RESULT
The SCST Duty cycle = No short control signalling

#### 802.11 n 40MHz

SHORT CONTROL SIGNALLING TRANSMISSION RESULT
The SCST Duty cycle = No short control signalling

SCST on time is 0ms

### 3.6. TRANSMITTER SPURIOUS EMISSIONS

#### 3.6.1. LIMITS OF TRANSMITTER SPURIOUS EMISSIONS

Transmitter limits for narrowband spurious emissions:

Frequency Range	Maximum Power Limit (e.r.p. ( $\leq 1$ GHz) e.i.r.p. ( $> 1$ GHz))	Bandwidth
30 MHz to 47 MHz	-36dBm	100kHz
47 MHz to 74 MHz	-54dBm	100kHz
74 MHz to 87,5 MHz	-36dBm	100kHz
87,5 MHz to 118 MHz	-54dBm	100kHz
118 MHz to 174 MHz	-36dBm	100kHz
174 MHz to 230 MHz	-54dBm	100kHz
230 MHz to 470 MHz	-36dBm	100kHz
470 MHz to 862 MHz	-54dBm	100kHz
862 MHz to 1 GHz	-36dBm	100kHz
1GHz ~ 12.75GHz	-30dBm	1MHz

Note: These limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

#### 3.6.2. TEST PROCEDURE

Refer to chapter 5.4.9.2 of ETSI EN 300 328 V2.1.1.

Measurement	
<input type="checkbox"/> Conducted measurement	<input checked="" type="checkbox"/> Radiated measurement
<p><u>For Conducted measurement:</u></p> <p>The level of unwanted emissions shall be measured as their power in a specified load (conducted spurious emissions) and their effective radiated power when radiated by the cabinet or structure of the equipment with the antenna connector(s) terminated by a specified load (cabinet radiation).</p>	
<p><u>Conducted measurement (For equipment with multiple transmit chains):</u></p> <p><input type="checkbox"/> Option 1: The results for each of the transmit chains for the corresponding 1MHz segments shall be added and compared with the limits.</p> <p><input type="checkbox"/> Option 2: The results for each of the transmit chains shall be individually compared with the limits after these limits have been reduced by <math>10 \times \log(N)</math> (number of active transmit chains)</p>	

### 3.6.3. DEVIATION FROM TEST STANDARD

No deviation.

### 3.6.4. TEST SETUP

1. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration).
2. The equipment was configured to operate under its worst case situation with respect to output power.
3. The measurement was performed at normal environmental conditions only. Controlling software has been activated to set the EUT on specific status.
4. This measurement was performed at the lowest and the highest channel.




### 3.6.5. TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA

##### 802.11b

FREQUENCY RANGE	30MHz ~ 1GHz	OPERATING CHANNEL	1
-----------------	--------------	-------------------	---

SPURIOUS EMISSION LEVEL				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
30.00	H	-83.40	-36.00	-47.40
49.40	H	-85.68	-54.00	-31.68
202.98	H	-69.18	-54.00	-15.18
264.42	H	-85.83	-36.00	-49.83
340.40	H	-93.08	-36.00	-57.08
450.33	H	-87.32	-36.00	-51.32






BUREAU  
VERITAS

Test Report No.: RE170623N070

FREQUENCY RANGE	30MHz ~ 1GHz	OPERATING CHANNEL	1
-----------------	--------------	-------------------	---

SPURIOUS EMISSION LEVEL				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
49.40	V	-76.13	-54.00	-22.13
96.28	V	-86.35	-54.00	-32.35
125.38	V	-88.65	-36.00	-52.65
212.68	V	-73.05	-54.00	-19.05
238.55	V	-74.05	-36.00	-38.05
264.42	V	-78.02	-36.00	-42.02





## ABOVE 1GHz WORST-CASE DATA

### 802.11b

<b>FREQUENCY RANGE</b>	1GHz ~ 12.75GHz	<b>OPERATING CHANNEL</b>	1, 13
------------------------	-----------------	--------------------------	-------

SPURIOUS EMISSION LEVEL					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
1	4824.02	V	-56.44	-30.00	-26.44
	4824.59	H	-58.34	-30.00	-28.34
	7235.11	V	-56.30	-30.00	-26.30
	7236.98	H	-56.71	-30.00	-26.71
13	4943.87	H	-58.23	-30.00	-28.23
	4944.01	V	-55.89	-30.00	-25.89
	7416.14	H	-56.93	-30.00	-26.93
	7416.38	V	-56.68	-30.00	-26.68

### 802.11g

<b>FREQUENCY RANGE</b>	1GHz ~ 12.75GHz	<b>OPERATING CHANNEL</b>	1, 13
------------------------	-----------------	--------------------------	-------

SPURIOUS EMISSION LEVEL					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
1	4824.88	H	-58.35	-30.00	-28.35
	4824.99	V	-58.14	-30.00	-28.14
	7235.99	H	-56.32	-30.00	-26.32
	7236.07	V	-56.36	-30.00	-26.36
13	4944.50	H	-58.67	-30.00	-28.67
	4944.97	V	-58.38	-30.00	-28.38
	7416.16	H	-57.24	-30.00	-27.24
	7416.47	V	-56.75	-30.00	-26.75

802.11n (20M)

<b>FREQUENCY RANGE</b>	1GHz ~ 12.75GHz	<b>OPERATING CHANNEL</b>	1, 13
------------------------	-----------------	--------------------------	-------

SPURIOUS EMISSION LEVEL					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
1	4823.56	H	-58.84	-30.00	-28.84
	4824.50	V	-58.46	-30.00	-28.46
	7236.51	V	-56.76	-30.00	-26.76
	7236.71	H	-56.47	-30.00	-26.47
13	4944.04	H	-59.20	-30.00	-29.20
	4944.66	V	-58.52	-30.00	-28.52
	7416.30	H	-57.47	-30.00	-27.47
	7416.56	V	-56.96	-30.00	-26.96

802.11n (40M)

<b>FREQUENCY RANGE</b>	1GHz ~ 12.75GHz	<b>OPERATING CHANNEL</b>	3, 11
------------------------	-----------------	--------------------------	-------

SPURIOUS EMISSION LEVEL					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
3	4844.67	H	-58.47	-30.00	-28.47
	4844.92	V	-58.20	-30.00	-28.20
	7265.32	H	-56.54	-30.00	-26.54
	7266.78	V	-56.99	-30.00	-26.99
11	4923.36	V	-58.40	-30.00	-28.40
	4923.76	H	-58.75	-30.00	-28.75
	7386.37	H	-56.68	-30.00	-26.68
	7386.95	V	-56.20	-30.00	-26.20

## RECEIVER PARAMETERS

### 3.7. RECEIVER SPURIOUS RADIATION

#### 3.7.1. LIMITS OF RECEIVER SPURIOUS RADIATION

Frequency Range	Maximum Power Limit (e.r.p. ( $\leq 1$ GHz) e.i.r.p. ( $> 1$ GHz))
30MHz ~ 1GHz	-57dBm
1GHz ~ 12.75GHz	-47dBm

Note: These limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

#### 3.7.2. TEST PROCEDURE

Refer to chapter 5.4.10.2 of ETSI EN 300 328 V2.1.1.

Measurement	
<input type="checkbox"/> Conducted measurement	<input checked="" type="checkbox"/> Radiated measurement
<p><u>For Conducted measurement:</u></p> <p>The level of unwanted emissions shall be measured as their power in a specified load (conducted spurious emissions) and their effective radiated power when radiated by the cabinet or structure of the equipment with the antenna connector(s) terminated by a specified load (cabinet radiation).</p>	
<p><u>Conducted measurement (For equipment with multiple transmit chains):</u></p> <p><input type="checkbox"/> Option 1: The results for each of the transmit chains for the corresponding 1MHz segments shall be added and compared with the limits.</p> <p><input type="checkbox"/> Option 2: The results for each of the transmit chains shall be individually compared with the limits after these limits have been reduced by <math>10 \times \log(N)</math> (number of active transmit chains)</p>	

#### 3.7.3. DEVIATION FROM TEST STANDARD

No deviation.

#### 3.7.4. TEST SETUP

1. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration).
2. Testing was performed when the equipment was in a receive-only mode.
3. The measurement was performed at normal environmental conditions only. Controlling software has been activated to set the EUT on specific status.
4. This measurement was performed at the lowest and the highest channel.




### 3.7.5. TEST RESULTS

#### RX WORST-CASE DATA


FREQUENCY RANGE	30MHz ~ 1GHz	OPERATING CHANNEL	1
-----------------	--------------	-------------------	---

SPURIOUS EMISSION LEVEL				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
30.00	H	-84.85	-57.00	-27.85
49.40	H	-86.29	-57.00	-29.29
<b>202.98</b>	<b>H</b>	<b>-71.64</b>	<b>-57.00</b>	<b>-14.64</b>
262.80	H	-86.31	-57.00	-29.31
450.33	H	-87.14	-57.00	-30.14
600.68	H	-85.60	-57.00	-28.60



<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz	<b>OPERATING CHANNEL</b>	1
------------------------	--------------	--------------------------	---

SPURIOUS EMISSION LEVEL				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
49.40	V	-75.99	-57.00	-18.99
127.00	V	-88.14	-57.00	-31.14
214.30	V	-73.04	-57.00	-16.04
266.03	V	-77.64	-57.00	-20.64
340.40	V	-87.56	-57.00	-30.56
450.33	V	-87.49	-57.00	-30.49



**RX ABOVE 1GHz DATA**

<b>FREQUENCY RANGE</b>	1GHz ~ 12.75GHz	<b>OPERATING CHANNEL</b>	1, 13
------------------------	-----------------	--------------------------	-------

SPURIOUS EMISSION LEVEL					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
1	3761.00	V	-57.45	-47.00	-10.45
	4075.00	H	-59.39	-47.00	-12.39
	5818.00	H	-59.19	-47.00	-12.19
	6346.00	V	-57.55	-47.00	-10.55
13	3291.00	V	-58.59	-47.00	-11.59
	3624.00	H	-58.17	-47.00	-11.17
	<b>5504.00</b>	<b>V</b>	<b>-57.04</b>	<b>-47.00</b>	<b>-10.04</b>
	6288.00	H	-57.55	-47.00	-10.55

### 3.8. RECEIVER BLOCKING

#### 3.8.1. LIMITS OF RECEIVER BLOCKING

This requirement applies to all receiver categories.

Receiver Category		
<input checked="" type="checkbox"/> Category 1(EIRP>10dBm)	<input type="checkbox"/> Category 2(EIRP ≤ 10dBm)	<input type="checkbox"/> Category 3(EIRP ≤ 0dBm)
Minimum performance criterion	<input checked="" type="checkbox"/> PER ≤ 10%	
	<input type="checkbox"/> Alternative performance criteria (See note)	
Note: The manufacturer was declared performance criteria is x% for the intended use of the equipment.		

Receiver Category 1 Equipment			
Wanted signal mean power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (See note 2)	Type of blocking signal
P <sub>min</sub> + 6 dB	2 380 2 503.5	-53	CW
P <sub>min</sub> + 6 dB	2 300 2 330 2 360	-47	CW
P <sub>min</sub> + 6 dB	2 523.5 2 553.5 2 583.5 2 613.5 2 643.5 2 673.5	-47	CW
NOTE 1: P <sub>min</sub> is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.			
NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.			

Receiver Category 2 Equipment			
Wanted signal mean power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (See note 2)	Type of blocking signal
P <sub>min</sub> + 6 dB	2 380 2 503.5	-57	CW
P <sub>min</sub> + 6 dB	2 300 2 583.5	-47	CW
NOTE 1: P <sub>min</sub> is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.			
NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.			

Receiver Category 3 Equipment			
Wanted signal mean power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (See note 2)	Type of blocking signal
$P_{min} + 12$ dB	2 380 2 503.5	-57	CW
$P_{min} + 12$ dB	2 300 2 583.5	-47	CW
NOTE 1: $P_{min}$ is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.			
NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.			

### 3.8.2. TEST PROCEDURE

Refer to chapter 5.4.11.2. of ETSI EN 300 328 V2.1.1.


Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

### 3.8.3. DEVIATION FROM TEST STANDARD

No deviation.



### 3.8.4. TEST SETUP CONFIGURATION





## 3.8.5. TEST RESULT

## 802.11b

## Receiver Category 1 Equipment

Receiver blocking performance when operating at the lowest operating channel(CH01)				
P <sub>min</sub> : -77.48dBm			antenna gain(G) : 5dBi	
The actual blocking signal power(Note1)			<input checked="" type="checkbox"/> at the antenna connector	
			<input type="checkbox"/> in front of the antenna	
Note1: For the conducted measurements , the level shall be corrected as follows: the actual blocking signal power = blocking signal power + antenna gain				
Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz))	The actual blocking signal power (dBm)	PER(%)	Pass/Fail
P <sub>min</sub> + 6 dB	2380	-48	1.1	PASS
	2503.5	-48	0.9	PASS
	2300	-42	0.7	PASS
	2330	-42	1.2	PASS
	2360	-42	1.7	PASS
	2523.5	-42	0.8	PASS
	2553.5	-42	1.2	PASS
	2583.5	-42	1.9	PASS
	2613.5	-42	0.9	PASS
	2643.5	-42	1.4	PASS
	2673.5	-42	1.6	PASS


Receiver blocking performance when operating at the Highest operating channel(CH13)				
P <sub>min</sub> : -77.48dBm			antenna gain(G) : 5dBi	
The actual blocking signal power(Note1)			<input checked="" type="checkbox"/> at the antenna connector	
			<input type="checkbox"/> in front of the antenna	
Note1: For the conducted measurements , the level shall be corrected as follows: the actual blocking signal power = blocking signal power + antenna gain				
Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz))	The actual blocking signal power (dBm)	PER(%)	Pass/Fail
P <sub>min</sub> + 6 dB	2380	-48	1.1	PASS
	2503.5	-48	0.9	PASS
	2300	-42	0.7	PASS
	2330	-42	1.2	PASS
	2360	-42	1.7	PASS
	2523.5	-42	0.8	PASS
	2553.5	-42	1.2	PASS
	2583.5	-42	1.9	PASS
	2613.5	-42	0.9	PASS
	2643.5	-42	1.4	PASS
	2673.5	-42	1.6	PASS

## 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

SPURIOUS EMISSION TEST BELOW 1GHz



### SPURIOUS EMISSION TEST ABOVE 1GHz





## RECEIVING BLOCKING





Test Report No.: RE170623N070

## 5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

--- END ---