

CE Radio Test Report

Project No. : 1702C180
Equipment : Wireless N300 Easy Setup Router
Model Name : F3
Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD
Address : 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road,
Nanshan District, Shenzhen, China. 518052

Date of Receipt : Feb. 24, 2017
Date of Test : Feb. 24, 2017 ~ Mar. 15, 2017
Issued Date : Mar. 16, 2017
Tested by : BTL Inc.

Testing Engineer : Shawn Xiao
(Shawn Xiao)

Technical Manager : David Mao
(David Mao)

Authorized Signatory : Steven Lu
(Steven Lu)

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	8
2 . RF EMISSIONS MEASUREMENT	9
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
2.3 TEST CHANNEL	9
2.4 TEST METHODOLOGY AND RESULTS	10
3 . GENERAL INFORMATION	11
3.1 GENERAL DESCRIPTION OF EUT	11
3.2 DESCRIPTION OF TEST MODES	13
3.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	14
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	15
3.5 DESCRIPTION OF SUPPORT UNITS	15
4 . RF OUTPUT POWER	16
4.1 APPLIED PROCEDURES / LIMIT	16
4.2 TEST PROCEDURES	16
4.3 TEST SETUP LAYOUT	16
4.4 TEST DEVIATION	16
4.5 EUT OPERATION DURING TEST	16
4.6 TEST RESULTS	16
5 . POWER SPECTRAL DENSITY	17
5.1 APPLIED PROCEDURES / LIMIT	17
5.2 TEST PROCEDURES	17
5.3 TEST SETUP LAYOUT	17
5.4 TEST DEVIATION	17
5.5 EUT OPERATION DURING TEST	17
5.6 TEST RESULTS	17
6 . DUTY CYCLE, TX-SEQUENCE, TX-GAP	18
6.1 APPLIED PROCEDURES / LIMIT	18
6.2 TEST PROCEDURES	18
6.3 TEST SETUP LAYOUT	18
6.4 TEST DEVIATION	18
6.5 EUT OPERATION DURING TEST	18

Table of Contents	Page
6.6 TEST RESULTS	18
7 . MEDIUM UTILISATION (MU) FACTOR	19
7.1 APPLIED PROCEDURES / LIMIT	19
7.2 TEST PROCEDURES	19
7.3 TEST SETUP LAYOUT	19
7.4 TEST DEVIATION	19
7.5 EUT OPERATION DURING TEST	19
7.6 TEST RESULTS	19
8 . ADAPTIVITY (ADAPTIVE EQUIPMENT USING MODULATIONS OTHER THAN FHSS)	20
8.1 APPLIED PROCEDURES / LIMIT	20
8.2 TEST PROCEDURES	23
8.3 TEST SETUP LAYOUT	23
8.4 TEST DEVIATION	23
8.5 EUT OPERATION DURING TEST	23
8.6 TEST RESULTS	23
9 . OCCUPIED CHANNEL BANDWIDTH	24
9.1 APPLIED PROCEDURES / LIMIT	24
9.2 TEST PROCEDURES	24
9.3 TEST SETUP LAYOUT	24
9.4 TEST DEVIATION	24
9.5 EUT OPERATION DURING TEST	24
9.6 TEST RESULTS	24
10 . TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN	25
10.1 APPLIED PROCEDURES / LIMIT	25
10.2 TEST PROCEDURES	25
10.3 TEST SETUP LAYOUT	26
10.4 TEST DEVIATION	26
10.5 EUT OPERATION DURING TEST	26
10.6 TEST RESULTS	26
11 . TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN	27
11.1 APPLIED PROCEDURES / LIMIT	27
11.2 TEST PROCEDURES	27

Table of Contents	Page
11.3 TEST SETUP LAYOUT	28
11.4 TEST DEVIATION	28
11.5 EUT OPERATION DURING TEST	28
11.6 TEST RESULTS	28
12 . RECEIVER SPURIOUS EMISSIONS	29
12.1 APPLIED PROCEDURES / LIMIT	29
12.2 TEST PROCEDURES	29
12.3 TEST SETUP LAYOUT	30
12.4 TEST DEVIATION	30
12.5 EUT OPERATION DURING TEST	30
12.6 TEST RESULTS	30
13 . RECEIVER BLOCKING	31
13.1 APPLIED PROCEDURES / LIMIT	31
13.2 TEST PROCEDURES	32
13.3 TEST SETUP LAYOUT	32
13.4 TEST DEVIATION	33
13.5 EUT OPERATION DURING TEST	33
13.6 TEST RESULTS	33
14 . INFORMATION AS REQUIRED BY EN 300 328 V2.1.1, CLAUSE 5.4.1	34
15 . MEASUREMENT INSTRUMENTS LIST	38
16 . EUT TEST PHOTO	41
ATTACHMENT A - RF OUTPUT POWER	42
ATTACHMENT B - POWER SPECTRAL DENSITY	45
ATTACHMENT C - DUTY CYCLE, TX-SEQUENCE, TX-GAP	54
ATTACHMENT D - MEDIUM UTILISATION (MU) FACTOR	55
ATTACHMENT E - ADAPTIVITY	56
ATTACHMENT F - OCCUPIED CHANNEL BANDWIDTH	78
ATTACHMENT G - TRANSMITTER UNWANTED EMISSIONS IN THE OOB DOMAIN	83
ATTACHMENT H - TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN	88

Table of Contents

Page

ATTACHMENT I - RECEIVER SPURIOUS EMISSIONS

113

ATTACHMENT J - RECEIVER BLOCKING

138

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-ETSP-1-1702C180	Original Issue	Mar. 16, 2017

1. CERTIFICATION

Equipment : Wireless N300 Easy Setup Router
Brand Name : Tenda
Model Name : F3
Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD
Manufacturer : SHENZHEN TENDA TECHNOLOGY CO.,LTD
Address : 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District,
Shenzhen, China. 518052
Date of Test : Feb. 24, 2017 ~ Mar. 15, 2017
Test Sample : Engineering Sample
Standard(s) : EN 300 328 V2.1.1 (2016-11)

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-ETSP-1-1702C180) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Test results included in this report is only for the WIFI 2.4GHz part.

2. RF EMISSIONS MEASUREMENT

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-CB12/OVEN** at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2 .The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

Parameter	Uncertainty
Occupied Channel Bandwidth	±5 %
RF Output Power, conducted	±1.5 dB
Power Spectral Density, conducted	±3 dB
Unwanted Emissions, conducted	±3 dB
All emissions, radiated	±6 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %

2.3 TEST CHANNEL

IEEE 802.11b/g/n(20 MHz)		
Test Channel	EUT Channel	Test Frequency (MHz)
low	CH01	2412
middle	CH07	2442
high	CH13	2472

IEEE 802.11n(40 MHz)		
Test Channel	EUT Channel	Test Frequency (MHz)
low	CH03	2422
middle	CH07	2442
high	CH11	2462

Note:

- (1) The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be stated by the supplier.

2.4 TEST METHODOLOGY AND RESULTS

Harmonised Standard ETSI EN 300 328 V2.1.1				
Essential Requirement			Requirement Conditionality	
No	Description	Reference: Clause No	U/C	Condition
1	RF Output Power	4.3.1.2 or 4.3.2.2	U	
2	Power Spectral Density	4.3.2.3	C	Only for equipment using wide band modulations other than FHSS
3	Duty cycle, Tx-Sequence, Tx-gap	4.3.1.3 or 4.3.2.4	C	Only for non-adaptive equipment and RF Output Power>10dBm
4	Accumulated Transmit time,, Frequency Occupation & Hopping Sequence	4.3.1.4	C	Only for FHSS equipment
5	Hopping Frequency Separation	4.3.1.5	C	Only for FHSS equipment
6	Medium Utilisation	4.3.1.6 or 4.3.2.5	C	Only for non-adaptive equipment and RF Output Power>10dBm
7	Adaptivity	4.3.1.7 or 4.3.2.6	C	Only for adaptive equipment and RF Output Power>10dBm
8	Occupied Channel Bandwidth	4.3.1.8 or 4.3.2.7	U	
9	Transmitter unwanted emissions in the OOB domain	4.3.1.9 or 4.3.2.8	U	
10	Transmitter unwanted emissions in the spurious domain	4.3.1.10 or 4.3.2.9	U	
11	Receiver spurious emissions	4.3.1.11 or 4.3.2.10	U	
12	Receiver Blocking	4.3.1.12 or 4.3.2.11	U	
13	Geo-location capability	4.3.1.13 or 4.3.2.12	C	Only for equipment with geo-location capability

NOTE:

- (1) "U/C": Indicates whether the requirement is unconditionally applicable (U) or is conditional upon the manufacturer's claimed functionality of the equipment (C).

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless N300 Easy Setup Router	
Brand Name	Tenda	
Model Name	F3	
Model Difference	N/A	
Power Source	DC Voltage supplied from AC/DC adapter. Model: BN049-A05009E	
Power Rating	I/P: 100-240Vac, 50/60Hz, 0.3A O/P: 9Vdc, 600mA	
Product Description	Operation Frequency	2412~2472MHz
	Modulation Technology	802.11b: DSSS 802.11g: OFDM 802.11n: OFDM
	Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n: up to 300 Mbps
	EIRP Power (Max.)	802.11b: 17.61 dBm 802.11g: 19.73 dBm 802.11n (20MHz): 19.84 dBm 802.11n (40MHz): 19.84 dBm

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

CH01 - CH13 for 802.11b, 802.11g, 802.11n(20MHz)					
CH03 - CH11 for 802.11n(40MHz)					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	06	2437	11	2462
02	2417	07	2442	12	2467
03	2422	08	2447	13	2472
04	2427	09	2452		
05	2432	10	2457		

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Dipole	N/A	5
2	N/A	N/A	Dipole	N/A	5

Note:

The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and receivers (2T2R).

4. The worst case for 1TX/ 2TX as follow:

Operating Mode TX Mode	1TX	2TX
802.11b	V (ANT 1)	-
802.11g	V (ANT 1)	-
802.11n(20MHz)	-	V (ANT 1 + ANT 2)
802.11n(40MHz)	-	V (ANT 1 + ANT 2)

ANT 1 for 1TX was found to be the worst case and recorded.

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Test Items	Mode	Data Rate	Channel
RF Output Power Power Spectral Density	IEEE 802.11b/CCK	1 Mbps	01/07/13
	IEEE 802.11g/BPSK	6 Mbps	01/07/13
	IEEE 802.11n(20MHz)/BPSK	MCS 8	01/07/13
	IEEE 802.11n(40MHz)/BPSK	MCS 8	03/07/11
Adaptivity, Occupied Channel Bandwidth Transmitter unwanted emissions in the OOB domain	IEEE 802.11b/CCK	1 Mbps	01/13
	IEEE 802.11g/BPSK	6 Mbps	01/13
	IEEE 802.11n(20MHz)/BPSK	MCS 8	01/13
	IEEE 802.11n(40MHz)/BPSK	MCS 8	03/11
Transmitter unwanted emissions in the spurious domain (30MHz~1GHz)	IEEE 802.11b/CCK	1 Mbps	01/13
	IEEE 802.11n(40MHz)/BPSK	MCS 8	03/11
Transmitter unwanted emissions in the spurious domain (1GHz~12.75GHz)	IEEE 802.11b/CCK	1 Mbps	01/07/13
	IEEE 802.11g/BPSK	6 Mbps	01/07/13
	IEEE 802.11n(20MHz)/BPSK	MCS 8	01/07/13
	IEEE 802.11n(40MHz)/BPSK	MCS 8	03/07/11
Receiver spurious emissions (30MHz~1GHz)	IEEE 802.11b/CCK	1 Mbps	01/13
	IEEE 802.11n(40MHz)/BPSK	MCS 8	03/11
Receiver spurious emissions (1GHz~12.75GHz)	IEEE 802.11b/CCK	1 Mbps	01/07/13
	IEEE 802.11g/BPSK	6 Mbps	01/07/13
	IEEE 802.11n(20MHz)/BPSK	MCS 8	01/07/13
	IEEE 802.11n(40MHz)/BPSK	MCS 8	03/07/11
Receiver Blocking	IEEE 802.11b/CCK	1 Mbps	01/13

3.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	N/A		
Frequency (MHz)	2412	2442	2472
IEEE 802.11b	26	27	28
IEEE 802.11g	34	35	36
IEEE 802.11n20	(30,34)	(31,31)	(31,31)
Frequency (MHz)	2422	2442	2462
IEEE 802.11n40	(33,36)	(35,35)	(35,35)

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	Notebook	Lenovo	INSPIRON 1420-	DOC	JX193A01SDC2

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.5m	DC Cable
2	NO	NO	10m	RJ-45 Cable

4. RF OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.2
Test Item	RF output power
Limit	For adaptive equipment using wide band modulations other than FHSS, the maximum RF output power shall be 20 dBm. The maximum RF output power for non-adaptive equipment shall be declared by the manufacturer and shall not exceed 20 dBm. See clause 5.4.1 m). For non-adaptive equipment using wide band modulations other than FHSS, the maximum RF output power shall be equal to or less than the value declared by the manufacturer.


4.2 TEST PROCEDURES

Please refer to chapter 5.4.2 of ETSI EN 300 328 V2.1.1.


Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input checked="" type="checkbox"/> Lowest, Middle and highest Channel	<input type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input type="checkbox"/> Normal	<input checked="" type="checkbox"/> Normal and Extreme

4.3 TEST SETUP LAYOUT

Normal Condition



Extreme Condition



4.4 TEST DEVIATION

There is no deviation with the original standard.

4.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

4.6 TEST RESULTS

Please refer to the Attachment A.

5. POWER SPECTRAL DENSITY

5.1 APPLIED PROCEDURES / LIMIT


Clause	4.3.2.3
Test Item	Power Spectral Density
Limit	For equipment using wide band modulations other than FHSS, the maximum Power Spectral Density is limited to 10 dBm per MHz.

5.2 TEST PROCEDURES

Please refer to chapter 5.4.3 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input checked="" type="checkbox"/> Lowest, Middle and highest Channel	<input type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

5.3 TEST SETUP LAYOUT



5.4 TEST DEVIATION

There is no deviation with the original standard.

5.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

5.6 TEST RESULTS

Please refer to the Attachment B.

6. DUTY CYCLE, TX-SEQUENCE, TX-GAP

6.1 APPLIED PROCEDURES / LIMIT


Clause	4.3.2.4
Test Item	Duty Cycle, Tx-sequence, Tx-gap
Limit	The Duty Cycle shall be equal to or less than the maximum value declared by the manufacturer. The Tx-sequence time shall be equal to or less than 10 ms. The minimum Tx-gap time following a Tx-sequence shall be equal to the duration of that proceeding Tx-sequence with a minimum of 3,5 ms.

6.2 TEST PROCEDURES

Please refer to chapter 5.4.2 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input checked="" type="checkbox"/> Lowest, Middle and highest Channel	<input type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

6.3 TEST SETUP LAYOUT



6.4 TEST DEVIATION

There is no deviation with the original standard.

6.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

6.6 TEST RESULTS

Please refer to the Attachment C.

7. MEDIUM UTILISATION (MU) FACTOR

7.1 APPLIED PROCEDURES / LIMIT


Clause	4.3.2.5
Test Item	Medium Utilisation (MU) factor
Limit	For non-adaptive equipment using wide band modulations other than FHSS, the maximum Medium Utilisation factor shall be 10 %.

7.2 TEST PROCEDURES

Please refer to chapter 5.4.2 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input checked="" type="checkbox"/> Lowest, Middle and highest Channel	<input type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

7.3 TEST SETUP LAYOUT



7.4 TEST DEVIATION

There is no deviation with the original standard.

7.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

7.6 TEST RESULTS

Please refer to the Attachment D.

8. ADAPTIVITY (ADAPTIVE EQUIPMENT USING MODULATIONS OTHER THAN FHSS)

8.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.6
Test Item	Adaptivity (adaptive equipment using modulations other than FHSS)
Limit	<p>Non-LBT based Detect and Avoid</p> <p>Equipment using a modulation other than FHSS and using the non-LBT based Detect and Avoid mechanism, shall comply with the following minimum set of requirements:</p> <ol style="list-style-type: none"> 1) During normal operation, the equipment shall evaluate the presence of a signal on its current operating channel. If it is determined that a signal is present with a level above the detection threshold defined in step 5), the channel shall be marked as 'unavailable'. 2) The channel shall remain unavailable for a minimum time equal to 1 s after which the channel may be considered again as an 'available' channel. 3) The total time during which an equipment has transmissions on a given channel without re-evaluating the availability of that channel, is defined as the Channel Occupancy Time. 4) The Channel Occupancy Time shall be less than 40 ms. Each such transmission sequence shall be followed by an Idle Period (no transmissions) of minimum 5 % of the Channel Occupancy Time with a minimum of 100 μs. After this, the procedure as in step 1) needs to be repeated. 5) The detection threshold shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the detection threshold level (TL) shall be equal or less than -70 dBm/MHz at the input to the receiver (assuming a 0 dBi receive antenna). For power levels below 20 dBm e.i.r.p., the detection threshold level may be relaxed to $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW}/P_{out})$. ($P_{out}$ in mW e.i.r.p.).

Limit	<p><u>LBT based Detect and Avoid</u></p> <p>The present document defines two types of adaptive equipment using wide band modulations other than FHSS and that uses an LBT based Detect and Avoid mechanism: Frame Based Equipment and Load Based Equipment. Adaptive equipment which is capable of operating as either Load Based Equipment or as Frame Based Equipment is allowed to switch dynamically between these types of operation.</p> <p><u>a. Frame Based Equipment</u></p> <p>Frame Based Equipment shall comply with the following requirements:</p> <ol style="list-style-type: none"> 1) Before transmission, the equipment shall perform a Clear Channel Assessment (CCA) check using energy detect. The equipment shall observe the operating channel for the duration of the CCA observation time which shall be not less than 18 μs. The channel shall be considered occupied if the energy level in the channel exceeds the threshold given in step 5) below. If the equipment finds the channel to be clear, it may transmit immediately. 2) If the equipment finds the channel occupied, it shall not transmit on this channel during the next Fixed Frame Period. NOTE 1: The equipment is allowed to switch to a non-adaptive mode and to continue transmissions on this channel providing it complies with the requirements applicable to non-adaptive equipment. See clause 4.3.2.6. Alternatively, the equipment is also allowed to continue Short Control Signaling Transmissions on this channel providing it complies with the requirements 4.3.2.6.4. 3) The total time during which an equipment has transmissions on a given channel without re-evaluating the availability of that channel, is defined as the Channel Occupancy Time. The Channel Occupancy Time shall be in the range 1 ms to 10 ms followed by an Idle Period of at least 5 % of the Channel Occupancy Time used in the equipment for the current Fixed Frame Period. 4) An equipment, upon correct reception of a packet which was intended for this equipment can skip CCA and immediately (see note 2) proceed with the transmission of management and control frames (e.g. ACK and Block ACK frames are allowed but data frames are not allowed). A consecutive sequence of such transmissions by the equipment without a new CCA shall not exceed the maximum Channel Occupancy Time. NOTE 2: For the purpose of multi-cast, the ACK transmissions (associated with the same data packet) of the individual devices are allowed to take place in a sequence. 5) The energy detection threshold for the CCA shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal or lower than -70 dBm/MHz at the input to the receiver (assuming a 0 dBi receive antenna). For power levels below 20 dBm e.i.r.p. the CCA threshold level may be relaxed to $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW}/P_{out})$. ($P_{out}$ in mW e.i.r.p.).
-------	---


Limit	<p><u>b. Load Based Equipment</u></p> <p>Load Based Equipment not using any of the mechanisms referenced above shall comply with the following minimum set of requirements:</p> <ol style="list-style-type: none"> 1) Before a transmission or a burst of transmissions, the equipment shall perform a Clear Channel Assessment (CCA) check using energy detect. The equipment shall observe the operating channel for the duration of the CCA observation time which shall be not less than 18 μs. The channel shall be considered occupied if the energy level in the channel exceeds the threshold given in step 5) below. If the equipment finds the channel to be clear, it may transmit immediately. 2) If the equipment finds the channel occupied, it shall not transmit on this channel (see note 2). The equipment shall perform an Extended CCA check in which the channel is observed for a random duration in the range between 18 μs and at least 160 μs. If the extended CCA check has determined the channel to be no longer occupied, the equipment may resume transmissions on this channel. If the Extended CCA time has determined the channel still to be occupied, it shall perform new Extended CCA checks until the channel is no longer occupied. NOTE 1: The Idle Period in between transmissions is considered to be the CCA or the Extended CCA check as there are no transmissions during this period. NOTE 2: The equipment is allowed to switch to a non-adaptive mode and to continue transmissions on this channel providing it complies with the requirements applicable to non-adaptive equipment. Alternatively, the equipment is also allowed to continue Short Control Signaling Transmissions on this channel providing it complies with the requirements given in clause 4.3.2.6.4. 3) The total time that an equipment makes use of a RF channel is defined as the Channel Occupancy Time shall be less than 13 ms, after which the device shall perform a new CCA described in step 1) above. 4) The equipment, upon correct reception of a packet which was intended for this equipment can skip CCA and immediately (see note 3) proceed with the transmission of management and control frames (e.g. ACK and Block ACK frames are allowed but data frames are not allowed). A consecutive sequence of transmissions by the equipment without a new CCA shall not exceed the maximum channel occupancy time as defined step in 3) above. NOTE 3: For the purpose of multi-cast, the ACK transmissions (associated with the same data packet) of the individual devices are allowed to take place in a sequence. 5) The energy detection threshold for the CCA shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal or lower than -70 dBm/MHz at the input to the receiver (assuming a 0 dBi receive antenna). For power levels below 20 dBm e.i.r.p., the CCA threshold level may be relaxed to $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10}(100 \text{ mW/Pout})$. (Pout in mW e.i.r.p). <p><u>Short Control Signalling Transmissions</u></p> <p>If implemented, Short Control Signalling Transmissions shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms or within an observation period equal to the dwell time, whichever is less.</p>
-------	---

8.2 TEST PROCEDURES

Please refer to chapter 5.4.6 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input type="checkbox"/> Lowest, Middle and highest Channel	<input checked="" type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

8.3 TEST SETUP LAYOUT



8.4 TEST DEVIATION

There is no deviation with the original standard.

8.5 EUT OPERATION DURING TEST

The measurements shall be performed during normal operation.

8.6 TEST RESULTS

Please refer to the Attachment E.

9. OCCUPIED CHANNEL BANDWIDTH

9.1 APPLIED PROCEDURES / LIMIT


Clause	4.3.2.7
Test Item	Occupied Channel Bandwidth
Limit	The Occupied Channel Bandwidth shall fall completely within the band given in clause 1. In addition, for non-adaptive systems using wide band modulations other than FHSS and with e.i.r.p greater than 10 dBm.

9.2 TEST PROCEDURES

Please refer to chapter 5.4.7 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input type="checkbox"/> Lowest, Middle and highest Channel	<input checked="" type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

9.3 TEST SETUP LAYOUT



9.4 TEST DEVIATION

There is no deviation with the original standard.

9.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

9.6 TEST RESULTS

Please refer to the Attachment F.

10. TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

10.1 APPLIED PROCEDURES / LIMIT


Clause	4.3.2.8
Test Item	Transmitter unwanted emissions in the out-of-band domain
Limit	<p>The transmitter unwanted emissions in the out-of-band domain but outside the allocated band, shall not exceed the values provided by the mask in below figure.</p> <p>A: -10 dBm/MHz e.i.r.p. B: -20 dBm/MHz e.i.r.p. C: Spurious Domain limits</p> <p>BW = Occupied Channel Bandwidth in MHz or 1 MHz whichever is greater</p>

10.2 TEST PROCEDURES

Please refer to chapter 5.4.8 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input type="checkbox"/> Lowest, Middle and highest Channel	<input checked="" type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

10.3 TEST SETUP LAYOUT



10.4 TEST DEVIATION

There is no deviation with the original standard.

10.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

10.6 TEST RESULTS

Please refer to the Attachment G.

11. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

11.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.9		
Test Item	Transmitter unwanted emissions in the spurious domain		
Limit	The transmitter unwanted emissions in the spurious domain shall not exceed the values given in below table. These limits are e.r.p for emissions up to 1GHz and e.i.r.p for emissions above 1GHz.		
	Frequency range	Maximum power	Bandwidth
	30 MHz to 47 MHz	-36 dBm	100 kHz
	47 MHz to 74 MHz	-54 dBm	100 kHz
	74 MHz to 87,5 MHz	-36 dBm	100 kHz
	87,5 MHz to 118 MHz	-54 dBm	100 kHz
	118 MHz to 174 MHz	-36 dBm	100 kHz
	174 MHz to 230 MHz	-54 dBm	100 kHz
	230 MHz to 470 MHz	-36 dBm	100 kHz
	470 MHz to 862 MHz	-54 dBm	100 kHz
	862 MHz to 1 GHz	-36 dBm	100 kHz
	1 GHz to 12,75 GHz	-30 dBm	1 MHz


11.2 TEST PROCEDURES

Please refer to chapter 5.4.9 of ETSI EN 300 328 V2.1.1.


Test Method	
<input type="checkbox"/> Conducted Measurement	<input checked="" type="checkbox"/> Radiated Measurement
Test Channels	
<input type="checkbox"/> Lowest, Middle and highest Channel	<input checked="" type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

11.3 TEST SETUP LAYOUT


Conducted Measurement



Radiated Measurement Test Set-Up Frequency Below 1 GHz



Radiated Measurement Test Set-Up Frequency Above 1 GHz



11.4 TEST DEVIATION

There is no deviation with the original standard.

11.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

11.6 TEST RESULTS

Please refer to the Attachment H

12. RECEIVER SPURIOUS EMISSIONS

12.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.10		
Test Item	Receiver spurious emissions		
Limit	The spurious emissions of the receiver shall not exceed the values given in below table.		
	These limits are e.r.p for emissions up to 1GHz and e.i.r.p for emissions above 1GHz.		
	Frequency range	Maximum power	Measurement bandwidth
	30 MHz to 1 GHz	-57 dBm	100 kHz
	1 GHz to 12,75 GHz	-47 dBm	1 MHz


12.2 TEST PROCEDURES

Please refer to chapter 5.4.10 of ETSI EN 300 328 V2.1.1.


Test Method	
<input type="checkbox"/> Conducted Measurement	<input checked="" type="checkbox"/> Radiated Measurement
Test Channels	
<input type="checkbox"/> Lowest, Middle and highest Channel	<input checked="" type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

12.3 TEST SETUP LAYOUT


Conducted Measurement



Radiated Measurement Test Set-Up Frequency Below 1 GHz



Radiated Measurement Test Set-Up Frequency Above 1 GHz



12.4 TEST DEVIATION

There is no deviation with the original standard.

12.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously receiving.

12.6 TEST RESULTS

Please refer to the Attachment I.

13. RECEIVER BLOCKING

13.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.11																
Test Item	Receiver Blocking																
Limit	While maintaining the minimum performance criteria as defined in clause 4.3.2.11.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined for the applicable receiver category provided in table 14, table 15 or table 16.																
	Receiver Category 1																
	Table 14 contains the Receiver Blocking parameters for Receiver Category 1 equipment.																
	Table 14: Receiver Blocking parameters for Receiver Category 1 equipment																
	<table><tr><th>Wanted signal mean power from companion device (dBm)</th><th>Blocking signal frequency (MHz)</th><th>Blocking signal power (dBm) (see note 2)</th><th>Type of blocking signal</th></tr><tr><td>$P_{min} + 6 \text{ dB}$</td><td>2 380 2 503,5</td><td>-53</td><td>CW</td></tr><tr><td>$P_{min} + 6 \text{ dB}$</td><td>2 300 2 330 2 360</td><td>-47</td><td>CW</td></tr><tr><td>$P_{min} + 6 \text{ dB}$</td><td>2 523,5 2 553,5 2 583,5 2 613,5 2 643,5 2 673,5</td><td>-47</td><td>CW</td></tr></table>	Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)	Type of blocking signal	$P_{min} + 6 \text{ dB}$	2 380 2 503,5	-53	CW	$P_{min} + 6 \text{ dB}$	2 300 2 330 2 360	-47	CW	$P_{min} + 6 \text{ dB}$	2 523,5 2 553,5 2 583,5 2 613,5 2 643,5 2 673,5	-47	CW
	Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)	Type of blocking signal													
	$P_{min} + 6 \text{ dB}$	2 380 2 503,5	-53	CW													
	$P_{min} + 6 \text{ dB}$	2 300 2 330 2 360	-47	CW													
	$P_{min} + 6 \text{ dB}$	2 523,5 2 553,5 2 583,5 2 613,5 2 643,5 2 673,5	-47	CW													
	NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.																
NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.																	
Receiver Category 2																	
Table 15 contains the Receiver Blocking parameters for Receiver Category 2 equipment.																	
Table 15: Receiver Blocking parameters receiver category 2 equipment																	
<table><tr><th>Wanted signal mean power from companion device (dBm)</th><th>Blocking signal frequency (MHz)</th><th>Blocking signal power (dBm) (see note 2)</th><th>Type of blocking signal</th></tr><tr><td>$P_{min} + 6 \text{ dB}$</td><td>2 380 2 503,5</td><td>-57</td><td>CW</td></tr><tr><td>$P_{min} + 6 \text{ dB}$</td><td>2 300 2 583,5</td><td>-47</td><td>CW</td></tr></table>	Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)	Type of blocking signal	$P_{min} + 6 \text{ dB}$	2 380 2 503,5	-57	CW	$P_{min} + 6 \text{ dB}$	2 300 2 583,5	-47	CW					
Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)	Type of blocking signal														
$P_{min} + 6 \text{ dB}$	2 380 2 503,5	-57	CW														
$P_{min} + 6 \text{ dB}$	2 300 2 583,5	-47	CW														
NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.																	
NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.																	


Limit	Receiver Category 3		
	Table 16 contains the Receiver Blocking parameters for Receiver Category 3 equipment.		
	Table 16: Receiver Blocking parameters receiver category 3 equipment		
	Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)
	$P_{min} + 12 \text{ dB}$	2 380 2 503,5	-57
	$P_{min} + 12 \text{ dB}$	2 300 2 583,5	-47
	NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.		
	NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.		

13.2 TEST PROCEDURES

Please refer to chapter 5.4.11 of ETSI EN 300 328 V2.1.1.

Test Method	
<input checked="" type="checkbox"/> Conducted Measurement	<input type="checkbox"/> Radiated Measurement
Test Channels	
<input type="checkbox"/> Lowest, Middle and highest Channel	<input checked="" type="checkbox"/> Lowest and highest Channel
<input type="checkbox"/> Two Adjacent Hopping Channel	<input type="checkbox"/> Two Hopping Channel
Environmental conditions	
<input checked="" type="checkbox"/> Normal	<input type="checkbox"/> Normal and Extreme

13.3 TEST SETUP LAYOUT



13.4 TEST DEVIATION

There is no deviation with the original standard.

13.5 EUT OPERATION DURING TEST

The measurements shall be performed during normal operation.

13.6 TEST RESULTS

Please refer to the Attachment J.

14. INFORMATION AS REQUIRED BY EN 300 328 V2.1.1, CLAUSE 5.4.1

In accordance with EN 300 328, clause 5.4.1, the following information is provided by the supplier.

14.1 The type of modulation used by the equipment:

- ☐ FHSS
☒ other forms of modulation

14.2 In case of FHSS modulation:

(1) In case of non-Adaptive Frequency Hopping equipment:

The number of Hopping Frequencies: N/A

(2) In case of Adaptive Frequency Hopping Equipment:

The maximum number of Hopping Frequencies: N/A

The minimum number of Hopping Frequencies: N/A

(3) The (average) Dwell Time: N/A

14.3 Adaptive / non-adaptive equipment:

- ☐ non-adaptive Equipment
☒ adaptive Equipment without the possibility to switch to a non-adaptive mode
☐ adaptive Equipment which can also operate in a non-adaptive mode

14.4 In case of adaptive equipment:

The Channel Occupancy Time implemented by the equipment: 1.12 ms

☒ The equipment has implemented an LBT based DAA mechanism

* In case of equipment using modulation different from FHSS:

- ☐ The equipment is Frame Based equipment
☒ The equipment is Load Based equipment
☐ The equipment can switch dynamically between Frame Based and Load Based

equipment

The CCA time implemented by the equipment: 124 μ s

- ☐ The equipment has implemented a non-LBT based DAA mechanism
☐ The equipment can operate in more than one adaptive mode

14.5 The worst case operational mode for each of the following tests:

- (1) RF Output Power: 19.84 dBm
- (2) Power Spectral Density: 9.97 dBm/MHz
- (3) Duty cycle, Tx-Sequence, Tx-gap: N/A
- (4) Accumulated Transmit time, Frequency Occupation & Hopping Sequence (only for FHSS equipment): N/A
- (5) Hopping Frequency Separation (only for FHSS equipment) : N/A
- (6) Medium Utilisation: N/A
- (7) Adaptivity: PASS, Receiver Blocking: PASS
- (8) Nominal Channel Bandwidth: 36.277 MHz
- (9) Transmitter unwanted emissions in the OOB domain: -26.02 dBm
- (10) Transmitter unwanted emissions in the spurious domain: -69.9200 dBm
- (11) Receiver spurious emissions: -49.6400 dBm

14.6 The different transmit operating modes (tick all that apply):

- ☐ Operating mode 1: Single Antenna Equipment
 - ☐ Equipment with only 1 antenna
 - ☐ Equipment with 2 diversity antennas but only 1 antenna active at any moment in time
 - ☐ Smart Antenna Systems with 2 or more antennas, but operating in a (legacy) mode where only 1 antenna is used. (e.g. IEEE 802.11™ [i.3] legacy mode in smart antenna systems)
- ☒ Operating mode 2: Smart Antenna Systems - Multiple Antennas without beam forming
 - ☒ Single spatial stream / Standard throughput / (e.g. IEEE 802.11™ [i.3] legacy mode)
 - ☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 1
 - ☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 2

NOTE: Add more lines if more channel bandwidths are supported.
- ☐ Operating mode 3: Smart Antenna Systems - Multiple Antennas with beam forming
 - ☐ Single spatial stream / Standard throughput (e.g. IEEE 802.11™ [i.3] legacy mode)
 - ☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 1
 - ☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 2

NOTE: Add more lines if more channel bandwidths are supported.

14.7 In case of Smart Antenna Systems:

(1) The number of Receive chains: 2

(2) The number of Transmit chains: 2

☒ symmetrical power distribution

☐ asymmetrical power distribution

In case of beam forming, the maximum (additional) beam forming gain: ____dBi

NOTE: The additional beam forming gain does not include the basic gain of a single antenna.

14.8 Operating Frequency Range(s) of the equipment:

(1) Operating Frequency Range 1: 2412 MHz to 2472 MHz

NOTE: Add more lines if more Frequency Ranges are supported.

14.9 Nominal Channel Bandwidth(s):

(1) Nominal Channel Bandwidth 1: 20 MHz

(2) Nominal Channel Bandwidth 2: 40 MHz

NOTE: Add more lines if more channel bandwidths are supported.

14.10 Type of Equipment (stand-alone, combined, plug-in radio device, etc.):

☒ Stand-alone

☐ Combined Equipment (Equipment where the radio part is fully integrated within another type of equipment)

☐ Plug-in radio device (Equipment intended for a variety of host systems)

☐ Other _____

14.11 The extreme operating conditions that apply to the equipment:

Operating temperature range: 0 ° C to 40 ° C

Details provided are for the: ☒ stand-alone equipment

☐ combined (or host) equipment

☐ test jig

14.12 The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices:

Details provided are for the: ☒ stand-alone equipment
☐ combined (or host) equipment
☐ test jig

Supply voltage ☐ AC Mains State AC voltage _____ V
☒ DC State AC voltage 100-240 V

In case of DC, indicate the type of power source

- ☐ Internal Power Supply
☒ External Power Supply or AC/DC adapter
☐ Battery
☐ Other: _____

14.13 Describe the test modes available which can facilitate testing:

The measurements shall be performed during continuously transmitting and normal operation.

14.14 The equipment type (e.g. Bluetooth[®], IEEE 802.11[™] [i.3], IEEE 802.15.4[™] [i.4], proprietary, etc.):

IEEE 802.11[™] [i.3]

15. MEASUREMENT INSTRUMENTS LIST

RF Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Sensor	Agilent	U2021XA	MY53020007	Jul. 31, 2017
2	Power Sensor	Agilent	U2021XA	MY53130004	Jul. 31, 2017
3	Power Sensor	Agilent	U2021XA	MY53260025	Jul. 31, 2017
4	Power Sensor	Agilent	U2021XA	MY53180019	Jul. 31, 2017
5	Usb Digitizer	Agilent	U2531A	5258020007	Jul. 31, 2017
6	Test Cable	emci	EMC104-SM-S M-9000(0.01G Hz-26.5GHz)	C-100	N/A
7	Test Cable	emci	EMC80-NM-N M-12000(9KHz -1GHz)	C-65	N/A
8	Const Temp. & Hu midity Chamber	Giant Force	ITH-225-20-S	IAB0309-001	Sep. 04, 2017
9	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Power Spectral Density					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	Test Cable	emci	EMC104-SM-S M-9000(0.01G Hz-26.5GHz)	C-100	N/A
3	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Adaptivity					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	MXG Vector Signal Generator	Agilent	N5172B	MY53050758	Mar. 27, 2017
3	MXG Analog Signal Generator	Agilent	N5181A	MY49060710	Oct. 10, 2017
4	Microflex Cable	NA	NA	1m	Jan. 17, 2017
5	POWER SPLITTER	Mimi-Circuits	ZFRSC-183-S +	SF601301339 -1	Mar. 09, 2018
6	POWER SPLITTER	Mimi-Circuits	ZN4PD1-63-S +	SF9335D1045 -2	Mar. 09, 2018
7	COUPLER	Mimi-Circuits	ZADC-10-63-S +	SF631801334	Feb. 22, 2018
8	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Occupied Channel Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	Test Cable	emci	EMC104-SM-S M-9000(0.01G Hz-26.5GHz)	C-100	N/A
3	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Transmitter Unwanted Out Of Band Domain					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	Test Cable	emci	EMC104-SM-S M-9000(0.01G Hz-26.5GHz)	C-100	N/A
3	Const Temp. & Humidity Chamber	Giant Force	ITH-225-20-S	IAB0309-001	Sep. 04, 2017
4	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Transmitter and Receiver Spurious Emission (Conducted Measurement)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	Test Cable	emci	EMC104-SM-S M-9000(0.01G Hz-26.5GHz)	C-100	N/A
3	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Transmitter and Receiver Spurious Emission (Radiated Measurement)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC012645B	980221	Dec. 04, 2016
3	Amplifier	Agilent	8449B	3008A02274	Nov. 01, 2017
4	Double Ridged Guide Antenna	ETS-LINDGREN	3115	00075846	Mar. 27, 2017
5	Antenna	SCHWARZBECK	VULB 9160	9160-3231	Mar. 27, 2017
6	Test Cable	emci	EMC104-SM-S M-9000(0.01G Hz-26.5GHz)	C-100	N/A
7	Test Cable	emci	EMC80-NM-N M-12000(9KHz -1GHz)	C-65	N/A
8	Controller	CT	SC100	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-0 1	N/A	N/A



Receiver Blocking

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 27, 2017
2	MXG Vector Signal Generator	Agilent	N5172B	MY53050758	Mar. 27, 2017
3	MXG Analog Signal Generator	Agilent	N5181A	MY49060710	Oct. 10, 2017
4	Microflex Cable	NA	NA	1m	Jan. 16, 2018
5	POWER SPLITTER	Mimi-Circuits	ZFRSC-183-S +	SF601301339 -1	Mar. 09, 2018
6	POWER SPLITTER	Mimi-Circuits	ZN4PD1-63-S +	SF9335D1045 -2	Mar. 09, 2018
7	COUPLER	Mimi-Circuits	ZADC-10-63-S +	SF631801334	Feb. 22, 2018
8	Measurement Software	Keysight	EN300328V19 1(V2.151229)	N/A	N/A

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

16. EUT TEST PHOTO

Radiated Measurement



ATTACHMENT A - RF OUTPUT POWER

Test Mode: TX Mode_ 802.11b Mode

Test Conditions		EIRP Power (dBm)			Number Of Bursts		
		CH01	CH07	CH13	CH01	CH07	CH13
T nom (°C)	25.00	17.26	17.55	17.61	11.00	11.00	11.00
T min (°C)	0.00	17.31	17.57	17.50	11.00	11.00	11.00
T max (°C)	40.00	17.15	17.49	17.43	11.00	11.00	11.00
Max EIRP Power		17.61			Min Number		11.00
Limits		20dBm (-10dBW)			≥ 10		
Result		Complies			Complies		

Test Mode: TX Mode_ 802.11g Mode

Test Conditions		EIRP Power (dBm)			Number Of Bursts		
		CH01	CH07	CH13	CH01	CH07	CH13
T nom (°C)	25.00	19.51	19.62	19.73	11.00	11.00	11.00
T min (°C)	0.00	19.60	19.58	19.68	11.00	11.00	11.00
T max (°C)	40.00	19.42	19.47	19.52	11.00	11.00	11.00
Max EIRP Power		19.73			Min Number		11.00
Limits		20dBm (-10dBW)			≥ 10		
Result		Complies			Complies		

Test Mode: TX Mode_ 802.11n 20M Mode

Test Conditions		EIRP Power (dBm)			Number Of Bursts		
		CH01	CH07	CH13	CH01	CH07	CH13
T nom (°C)	25.00	19.73	19.66	19.78	11.00	11.00	11.00
T min (°C)	0.00	19.76	19.74	19.84	11.00	11.00	11.00
T max (°C)	40.00	19.62	19.58	19.72	11.00	11.00	11.00
Max EIRP Power		19.84			Min Number		11.00
Limits		20dBm (-10dBW)			≥ 10		
Result		Complies			Complies		

Test Mode: TX Mode_ 802.11n 40M Mode


Test Conditions		EIRP Power (dBm)			Number Of Bursts		
		CH03	CH07	CH11	CH03	CH07	CH11
T nom (°C)	25.00	19.77	19.81	19.71	11.00	11.00	11.00
T min (°C)	0.00	19.64	19.74	19.84	11.00	11.00	11.00
T max (°C)	40.00	19.57	19.60	19.67	11.00	11.00	11.00
Max EIRP Power		19.84			Min Number		11.00
Limits		20dBm (-10dBW)			≥ 10		
Result		Complies			Complies		

Note: EIRP Power = output power conducted + G ant


ATTACHMENT B - POWER SPECTRAL DENSITY

Test Mode:	TX Mode_ 802.11b Mode
------------	-----------------------


Frequency (MHz)	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2412	9.73	10.00	Pass
2442	9.97	10.00	Pass
2472	9.79	10.00	Pass



802.11b Mode 2442




802.11b Mode 2472




Test Mode:	TX Mode_ 802.11g Mode
------------	-----------------------

Frequency (MHz)	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2412	7.72	10.00	Pass
2442	7.84	10.00	Pass
2472	7.96	10.00	Pass



802.11g Mode 2442



PSD Calculate

Refresh

Test Memo


Power Spectral Density

Max PSD Level (dBm / MHz) : 7.84

Test Result : Pass

*The Power Spectral Density must less then 10 dBm/MHz

802.11g Mode 2472



PSD Calculate

Refresh

Test Memo

Power Spectral Density

Max PSD Level (dBm / MHz) : 7.96


Test Result : Pass

*The Power Spectral Density must less then 10 dBm/MHz


Test Mode:

TX Mode_ 802.11n 20M Mode


Frequency (MHz)	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2412	7.82	10.00	Pass
2442	7.64	10.00	Pass
2472	7.70	10.00	Pass



802.11n 20M Mode 2442




802.11n 20M Mode 2472




Test Mode:

TX Mode_ 802.11n 40M Mode


Frequency (MHz)	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2422	5.05	10.00	Pass
2442	4.98	10.00	Pass
2462	4.84	10.00	Pass



802.11n 40M Mode 2442



802.11n 40M Mode 2462



ATTACHMENT C - DUTY CYCLE, TX-SEQUENCE, TX-GAP

Test Mode: N/A

Note: "N/A" denotes test is not applicable to this device.

ATTACHMENT D - MEDIUM UTILISATION (MU) FACTOR

Test Mode: N/A

Note: "N/A" denotes test is not applicable to this device.

ATTACHMENT E - ADAPTIVITY

1. List of measurements

UUT Operational Mode	Frame Based Equipment	
	Load Based Equipment (CCA using 'energy detect')	✓
	Load Based Equipment (CCA not using any of the mechanisms referenced)	

Clause	Test Parameter	Remarks	Pass / Fail
4.3.2.6.3.2.2	Adaptive (Frame Based Equipment)	Not Applicable	N/A
4.3.2.6.3.2.3	Adaptive (Load Based Equipment)	Applicable	Pass
4.3.2.6.4	Short Control Signaling Transmissions	Applicable	Pass

Test Mode: TX Mode_ 802.11b Mode

Channel Occupancy Time and Clear Channel Assessment Measured Results

Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2412	1.12	76.00
2472	1.12	86.00
Limit	13	18~160

Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.




Adaptivity

Adaptivity Detection Threshold Level	2412 MHz	-67.31 dBm/MHz
	2472 MHz	-67.61 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2412	Pass	3.235
2472	Pass	1.74
Limit	N/A	5
Result	Pass	


Note: Threshold Level = $-70 \text{ dBm/MHz} + (20 \text{ dBm} - P_{\text{out e.i.r.p}})/1 \text{ MHz}$ (P_{out} in dBm).
Short Control Signalling Transmissions = $50 \text{ (ms)} * \text{Duty cycle (\%)}$

802.11b Mode 2412

Adaptivity Measurement




CCA Time Info	DIFS / PIFS (us) : 106.00	SIFS (us) : 15.00
Maximum CCA time should between 18us ~ 180us	Measured CCA (us) : 76.00	



COT Time Info

Max Channel Occupancy Time (ms) : 1.12

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info




Test Result : Pass

Duty Cycle (%) : 6.47


*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

802.11b Mode 2472

Adaptivity Measurement




CCA Time Info	DIFS / PIFS (us) : 116.00	SIFS (us) : 15.00
Maximum CCA time should between 18us ~ 160us	Measured CCA (us) : 86.00	



COT Time Info

Max Channel Occupancy Time (ms) : 1.12

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info

Test Result : Pass

Duty Cycle (%) : 3.48

*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

Test Mode: TX Mode_ 802.11g Mode

Channel Occupancy Time and Clear Channel Assessment Measured Results

Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2412	0.21	124.00
2472	0.21	67.00
Limit	13	18~160

Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.




Adaptivity

Adaptivity Detection Threshold Level	2412 MHz	-69.60 dBm/MHz
	2472 MHz	-69.73 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2412	Pass	4.975
2472	Pass	2.735
Limit	N/A	5
Result	Pass	


Note: Threshold Level = $-70 \text{ dBm/MHz} + (20 \text{ dBm} - P_{\text{out e.i.r.p}})/1 \text{ MHz}$ (P_{out} in dBm).
Short Control Signalling Transmissions = 50 (ms) * Duty cycle (%)

802.11g Mode 2412

Adaptivity Measurement



CCA Time Info	DIFS / PIFS (us) : 148.00	SIFS (us) : 12.00
Maximum CCA time should between 18us ~ 160us	Measured CCA (us) : 124.00	



COT Time Info

Max Channel Occupancy Time (ms) : 0.21

*Please make sure the COT less than 1ms, or it will be failed.



Duty Cycle Info




Test Result : Pass

Duty Cycle (%) : 9.95

*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

802.11g Mode 2472

Adaptivity Measurement




CCA Time Info

Maximum CCA time should between 18us ~ 100us

DIFS / PIFS (us) : 91.00

SIFS (us) : 12.00

Measured CCA (us) : 67.00



COT Time Info

Max Channel Occupancy Time (ms) : 0.21

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info

Test Result : Pass

Duty Cycle (%) : 5.47

*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

Test Mode: TX Mode_ 802.11n 20M Mode

Channel Occupancy Time and Clear Channel Assessment Measured Results

Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2412	0.65	19.00
2472	1.81	48.00
Limit	13	18~160

Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.




Adaptivity

Adaptivity Detection Threshold Level	2412 MHz	-69.76 dBm/MHz
	2472 MHz	-69.84 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2412	Pass	2.49
2472	Pass	2.49
Limit	N/A	5
Result	Pass	


Note: Threshold Level = $-70 \text{ dBm/MHz} + (20 \text{ dBm} - P_{\text{out e.i.r.p}})/1 \text{ MHz}$ (P_{out} in dBm).
Short Control Signalling Transmissions = $50 \text{ (ms)} * \text{Duty cycle (\%)}$

802.11n 20M Mode 2412

Adaptivity Measurement




CCA Time Info	DIFS / PIFS (us) : 142.00	SIFS (us) : 16.00
Maximum CCA time should between 28us ~ 180us	Measured CCA (us) : 110.00	



COT Time Info

Max Channel Occupancy Time (ms) : 0.65

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info




Test Result : Pass

Duty Cycle (%) : 4.98


*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

802.11n 20M Mode 2472

Adaptivity Measurement




CCA Time Info	DIFS / PIFS (us) : 80.00	SIFS (us) : 16.00
Maximum CCA time should between 18us ~ 160us	Measured CCA (us) : 48.00	



COT Time Info

Max Channel Occupancy Time (ms) : 1.81

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info

Test Result : Pass

Duty Cycle (%) : 4.98

*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

Test Mode: TX Mode_ 802.11n 40M Mode

Channel Occupancy Time and Clear Channel Assessment Measured Results

Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2422	1.55	102.00
2462	1.55	102.00
Limit	13	18~160

Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.




Adaptivity & Receiver Blocking

Adaptivity Detection Threshold Level	2422 MHz	-69.77 dBm/MHz
	2462 MHz	-69.84 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2422	Pass	3.485
2462	Pass	3.98
Limit	N/A	5
Result	Pass	


Note: Threshold Level = -70 dBm/MHz + (20 dBm - Pout e.i.r.p)/1 MHz (Pout in dBm).
Short Control Signalling Transmissions = 50 (ms) * Duty cycle (%)

802.11n 40M Mode 2422

Adaptivity Measurement




CCA Time Info		
Maximum CCA time should between 18us ~ 160us	DIFS / PIFS (us) : 134.00	SIFS (us) : 16.00
	Measured CCA (us) : 102.00	



COT Time Info

Max Channel Occupancy Time (ms) : 1.55

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info




Test Result : Pass

Duty Cycle (%) : 6.97

*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

802.11n 40M Mode 2462

Adaptivity Measurement




CCA Time Info

Maximum CCA time should between 18us ~ 180us

DIFS / PIFS (us) : 134.00

SIFS (us) : 16.00


Measured CCA (us) : 102.00



COT Time Info

Max Channel Occupancy Time (ms) : 1.55

*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info

Test Result : Pass

Duty Cycle (%) : 7.96


*The Duty Cycle must less than 10% in every 50ms after AWGN signal was on.

ATTACHMENT F - OCCUPIED CHANNEL BANDWIDTH


Test Mode:	TX Mode_ 802.11b Mode
------------	-----------------------

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F _L at 99% BW (MHz)	F _H at 99% BW (MHz)	Result
2412	15.155	2404.42	-	Pass
2472	15.187	-	2479.59	
N/A		F _L >2400	F _H <2483.5	

802.11b Mode_2412




802.11b Mode_2472



Test Mode: TX Mode_ 802.11g Mode

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F _L at 99% BW (MHz)	F _H at 99% BW (MHz)	Result
2412	16.636	2403.68	-	Pass
2472	16.632	-	2480.32	
N/A		F _L >2400	F _H <2483.5	

802.11g Mode_2412



Occupied Bandwidth (MHz) : 16.636


Left Frequency (MHz) : 2403.67

Test Result : Pass

Limit : > 2400 MHz

Right Frequency (MHz) : 2420.30

802.11g Mode_2472



Occupied Bandwidth (MHz) : 16.632

Left Frequency (MHz) : 2463.66

Test Result : Pass


Limit : < 2483.5 MHz

Right Frequency (MHz) : 2480.30

Test Mode: TX Mode_ 802.11n 20M Mode

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F _L at 99% BW (MHz)	F _H at 99% BW (MHz)	Result
2412	17.817	2403.09	-	Pass
2472	17.819	-	2480.91	
N/A		F _L >2400	F _H <2483.5	

802.11n 20M Mode_2412



Occupied Bandwidth (MHz) : 17.817


Left Frequency (MHz) : 2403.08

Test Result : Pass

Limit : > 2400 MHz

Right Frequency (MHz) : 2420.90

802.11n 20M Mode_2472



Occupied Bandwidth (MHz) : 17.819

Left Frequency (MHz) : 2463.07

Test Result : Pass


Limit : < 2483.5 MHz

Right Frequency (MHz) : 2480.89

Test Mode: TX Mode_ 802.11n 40M Mode

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F _L at 99% BW (MHz)	F _H at 99% BW (MHz)	Result
2422	36.277	2403.86	-	Pass
2462	36.234	-	2480.12	
N/A		F _L >2400	F _H <2483.5	

802.11n 40M Mode_2422



Occupied Bandwidth (MHz): 36.277


Left Frequency (MHz): 2403.84

Test Result : Pass

Limit : > 2400 MHz

Right Frequency (MHz): 2440.12

802.11n 40M Mode_2462



Occupied Bandwidth (MHz): 36.234

Left Frequency (MHz): 2443.88

Test Result : Pass


Limit : < 2483.5 MHz

Right Frequency (MHz): 2480.11

ATTACHMENT G - TRANSMITTER UNWANTED EMISSIONS IN THE OOB DOMAIN

Test Mode: TX Mode_ 802.11b Mode_ Normal Temperature

802.11b Mode_2412




OOB Calculate

Memo

Out of Band Test Info

Test Result : Pass

802.11b Mode_2472



OOB Calculate


Memo

Out of Band Test Info

Test Result : Pass

Test Mode: TX Mode_ 802.11g Mode_ Normal Temperature

802.11g Mode_2412




OOB Calculate

Memo

Out of Band Test Info

Test Result : Pass

802.11g Mode_2472



OOB Calculate

Memo


Out of Band Test Info

Test Result : Pass

For 2TX

Test Mode: TX Mode_ 802.11n 20M Mode_ Normal Temperature


802.11n 20M Mode_2412



Out of Band Test Info

Test Result : Pass

802.11n 20M Mode_2472




Out of Band Test Info

Test Result : Pass

Test Mode: TX Mode_ 802.11n 40M Mode_ Normal Temperature

802.11n 40M Mode_2422




OOB Calculate

Memo

Out of Band Test Info

Test Result : Pass

802.11n 40M Mode_2462



OOB Calculate

Memo


Out of Band Test Info

Test Result : Pass

ATTACHMENT H - TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

Test Mode: TX Mode 2412 MHz (11b)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.02	-3.15	-72.17	-36.00	-36.17	RMS	
2	253.8760	-63.99	-3.06	-67.05	-36.00	-31.05	RMS	
3	322.5520	-64.68	-0.55	-65.23	-36.00	-29.23	RMS	
4	399.9580	-68.41	-0.09	-68.50	-36.00	-32.50	RMS	
5	465.7240	-68.43	2.36	-66.07	-36.00	-30.07	RMS	
6 *	786.2120	-78.67	8.28	-70.39	-54.00	-16.39	RMS	

Test Mode: TX Mode 2412 MHz (11b)


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	241.0720	-67.62	-2.43	-70.05	-36.00	-34.05	RMS	
2	326.5290	-69.78	-1.37	-71.15	-36.00	-35.15	RMS	
3	399.9580	-68.17	1.12	-67.05	-36.00	-31.05	RMS	
4	465.7240	-68.29	2.14	-66.15	-36.00	-30.15	RMS	
5	628.9750	-78.50	6.19	-72.31	-54.00	-18.31	RMS	
6 *	786.2120	-80.22	8.38	-71.84	-54.00	-17.84	RMS	

Test Mode: TX Mode 2472 MHz (11b)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.53	-3.15	-72.68	-36.00	-36.68	RMS	
2	266.0010	-63.63	-3.21	-66.84	-36.00	-30.84	RMS	
3	334.6770	-64.85	-0.60	-65.45	-36.00	-29.45	RMS	
4	399.9580	-67.99	-0.09	-68.08	-36.00	-32.08	RMS	
5	465.7240	-68.71	2.36	-66.35	-36.00	-30.35	RMS	
6 *	786.2120	-78.20	8.28	-69.92	-54.00	-15.92	RMS	

Test Mode: TX Mode 2472 MHz (11b)


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.46	-3.50	-72.96	-36.00	-36.96	RMS	
2	241.0720	-66.66	-2.43	-69.09	-36.00	-33.09	RMS	
3	322.5520	-69.10	-1.40	-70.50	-36.00	-34.50	RMS	
4	399.9580	-68.35	1.12	-67.23	-36.00	-31.23	RMS	
5	465.7240	-68.52	2.14	-66.38	-36.00	-30.38	RMS	
6 *	621.0210	-78.85	6.69	-72.16	-54.00	-18.16	RMS	

Test Mode: TX Mode 2422 MHz (11n 40M)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-70.01	-3.15	-73.16	-36.00	-37.16	RMS	
2	258.4350	-58.19	-3.09	-61.28	-36.00	-25.28	RMS	
3	322.5520	-64.29	-0.55	-64.84	-36.00	-28.84	RMS	
4	399.9580	-67.79	-0.09	-67.88	-36.00	-31.88	RMS	
5	465.7240	-69.19	2.36	-66.83	-36.00	-30.83	RMS	
6 *	776.2209	-78.53	8.40	-70.13	-54.00	-16.13	RMS	

Test Mode: TX Mode 2422 MHz (11n 40M)


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.57	-3.50	-73.07	-36.00	-37.07	RMS	
2	241.0720	-66.83	-2.43	-69.26	-36.00	-33.26	RMS	
3	322.5520	-69.20	-1.40	-70.60	-36.00	-34.60	RMS	
4	399.9580	-68.41	1.12	-67.29	-36.00	-31.29	RMS	
5	465.7240	-68.83	2.14	-66.69	-36.00	-30.69	RMS	
6 *	620.9240	-79.04	6.70	-72.34	-54.00	-18.34	RMS	

Test Mode: TX Mode 2462 MHz (11n 40M)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.43	-3.15	-72.58	-36.00	-36.58	RMS	
2	253.8760	-63.59	-3.06	-66.65	-36.00	-30.65	RMS	
3	322.5520	-64.62	-0.55	-65.17	-36.00	-29.17	RMS	
4	399.9580	-68.35	-0.09	-68.44	-36.00	-32.44	RMS	
5	465.7240	-67.88	2.36	-65.52	-36.00	-29.52	RMS	
6 *	786.2120	-78.22	8.28	-69.94	-54.00	-15.94	RMS	

Test Mode: TX Mode 2462 MHz (11n 40M)


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.55	-3.50	-73.05	-36.00	-37.05	RMS	
2	241.0720	-67.32	-2.43	-69.75	-36.00	-33.75	RMS	
3	399.9580	-68.28	1.12	-67.16	-36.00	-31.16	RMS	
4	465.7240	-68.40	2.14	-66.26	-36.00	-30.26	RMS	
5	628.9750	-78.57	6.19	-72.38	-54.00	-18.38	RMS	
6 *	786.2120	-79.85	8.38	-71.47	-54.00	-17.47	RMS	

Test Mode:	TX Mode 2412 MHz (11b)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.2290	-65.64	8.36	-57.28	-30.00	-27.28	RMS	
2 *	9648.0970	-60.35	12.93	-47.42	-30.00	-17.42	RMS	

Test Mode:	TX Mode 2412 MHz (11b)
------------	------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.0680	-63.92	8.37	-55.55	-30.00	-25.55	RMS	
2 *	9647.9570	-61.45	12.90	-48.55	-30.00	-18.55	RMS	

Test Mode:	TX Mode 2472 MHz (11b)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.3030	-65.39	8.36	-57.03	-30.00	-27.03	RMS	
2 *	9887.9040	-60.32	13.03	-47.29	-30.00	-17.29	RMS	

Test Mode:	TX Mode 2472 MHz (11b)
------------	------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.0680	-63.67	8.37	-55.30	-30.00	-25.30	RMS	
2 *	9887.9509	-61.87	13.15	-48.72	-30.00	-18.72	RMS	

Test Mode:	TX Mode 2412 MHz (11g)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.9590	-67.74	8.36	-59.38	-30.00	-29.38	RMS	
2 *	9648.1710	-60.14	12.93	-47.21	-30.00	-17.21	RMS	

Test Mode:	TX Mode 2412 MHz (11g)
------------	------------------------


Horizontal



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	Level	Factor	ment			Detector	Comment
		dBm	dB	dBm	dBm	dB		
1	4999.9620	-63.34	8.37	-54.97	-30.00	-24.97	RMS	
2 *	9647.9320	-61.30	12.90	-48.40	-30.00	-18.40	RMS	

Test Mode:	TX Mode 2472 MHz (11g)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.8780	-64.49	8.36	-56.13	-30.00	-26.13	RMS	
2 *	9887.9000	-60.62	13.03	-47.59	-30.00	-17.59	RMS	

Test Mode:	TX Mode 2472 MHz (11g)
------------	------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.7930	-68.16	8.37	-59.79	-30.00	-29.79	RMS	
2 *	9887.9290	-62.31	13.15	-49.16	-30.00	-19.16	RMS	

Test Mode:	TX Mode 2412 MHz (11n 20M)
------------	----------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.2250	-65.13	8.36	-56.77	-30.00	-26.77	RMS	
2 *	9647.9070	-59.69	12.93	-46.76	-30.00	-16.76	RMS	

Test Mode:	TX Mode 2412 MHz (11n 20M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.8920	-63.62	8.37	-55.25	-30.00	-25.25	RMS	
2 *	9648.0000	-62.75	12.90	-49.85	-30.00	-19.85	RMS	

Test Mode:	TX Mode 2472 MHz (11n 20M)
------------	----------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.9330	-65.43	8.36	-57.07	-30.00	-27.07	RMS	
2 *	9887.9300	-60.64	13.03	-47.61	-30.00	-17.61	RMS	

Test Mode:	TX Mode 2472 MHz (11n 20M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.9160	-63.50	8.37	-55.13	-30.00	-25.13	RMS	
2 *	9887.9060	-61.84	13.15	-48.69	-30.00	-18.69	RMS	

Test Mode: TX Mode 2422 MHz (11n 40M)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.8050	-65.62	8.36	-57.26	-30.00	-27.26	RMS	
2 *	9688.0610	-60.15	12.94	-47.21	-30.00	-17.21	RMS	

Test Mode:	TX Mode 2422 MHz (11n 40M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.1830	-63.44	8.37	-55.07	-30.00	-25.07	RMS	
2 *	9688.0679	-62.37	12.95	-49.42	-30.00	-19.42	RMS	

Test Mode:	TX Mode 2462 MHz (11n 40M)
------------	----------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.9880	-65.03	8.36	-56.67	-30.00	-26.67	RMS	
2 *	9848.0180	-60.58	13.01	-47.57	-30.00	-17.57	RMS	

Test Mode:	TX Mode 2462 MHz (11n 40M)
------------	----------------------------

Horizontal




No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	4999.8700	-63.32	8.37	-54.95	-30.00	-24.95	RMS	
2 *	9847.9530	-62.01	13.11	-48.90	-30.00	-18.90	RMS	

ATTACHMENT I - RECEIVER SPURIOUS EMISSIONS

Test Mode: RX Mode 2412 MHz (11b)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.74	-3.15	-72.89	-57.00	-15.89	RMS	
2	253.8760	-63.95	-3.06	-67.01	-57.00	-10.01	RMS	
3 *	310.5040	-62.31	-0.80	-63.11	-57.00	-6.11	RMS	
4	399.9890	-66.84	-0.09	-66.93	-57.00	-9.93	RMS	
5	465.7240	-68.87	2.36	-66.51	-57.00	-9.51	RMS	
6	786.2120	-77.56	8.28	-69.28	-57.00	-12.28	RMS	

Test Mode: RX Mode 2412 MHz (11b)


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.42	-3.50	-72.92	-57.00	-15.92	RMS	
2	241.0720	-67.18	-2.43	-69.61	-57.00	-12.61	RMS	
3	314.4040	-68.37	-1.55	-69.92	-57.00	-12.92	RMS	
4	399.9849	-65.96	1.12	-64.84	-57.00	-7.84	RMS	
5 *	465.7490	-66.45	2.14	-64.31	-57.00	-7.31	RMS	
6	621.0210	-78.48	6.69	-71.79	-57.00	-14.79	RMS	

Test Mode: RX Mode 2472 MHz (11b)


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.48	-3.15	-72.63	-57.00	-15.63	RMS	
2	253.8760	-63.79	-3.06	-66.85	-57.00	-9.85	RMS	
3 *	326.6260	-64.92	-0.57	-65.49	-57.00	-8.49	RMS	
4	399.9580	-68.21	-0.09	-68.30	-57.00	-11.30	RMS	
5	465.7240	-68.66	2.36	-66.30	-57.00	-9.30	RMS	
6	786.1150	-78.79	8.28	-70.51	-57.00	-13.51	RMS	

Test Mode: RX Mode 2472 MHz (11b)


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.15	-3.50	-72.65	-57.00	-15.65	RMS	
2	241.0720	-67.56	-2.43	-69.99	-57.00	-12.99	RMS	
3	322.5520	-69.53	-1.40	-70.93	-57.00	-13.93	RMS	
4	399.9580	-68.05	1.12	-66.93	-57.00	-9.93	RMS	
5 *	465.7240	-68.87	2.14	-66.73	-57.00	-9.73	RMS	
6	786.2120	-79.94	8.38	-71.56	-57.00	-14.56	RMS	

Test Mode:	RX Mode 2422 MHz (11n 40M)
------------	----------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.49	-3.15	-72.64	-57.00	-15.64	RMS	
2	253.8760	-63.05	-3.06	-66.11	-57.00	-9.11	RMS	
3 *	322.5520	-64.37	-0.55	-64.92	-57.00	-7.92	RMS	
4	399.9580	-68.12	-0.09	-68.21	-57.00	-11.21	RMS	
5	465.7240	-68.92	2.36	-66.56	-57.00	-9.56	RMS	
6	776.2209	-77.08	8.40	-68.68	-57.00	-11.68	RMS	

Test Mode:	RX Mode 2422 MHz (11n 40M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.60	-3.50	-73.10	-57.00	-16.10	RMS	
2	235.0580	-66.16	-2.74	-68.90	-57.00	-11.90	RMS	
3	322.5520	-69.13	-1.40	-70.53	-57.00	-13.53	RMS	
4	399.9580	-68.22	1.12	-67.10	-57.00	-10.10	RMS	
5 *	465.7240	-68.61	2.14	-66.47	-57.00	-9.47	RMS	
6	620.9240	-79.10	6.70	-72.40	-57.00	-15.40	RMS	

Test Mode:	RX Mode 2462 MHz (11n 40M)
------------	----------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	157.1670	-72.09	-1.07	-73.16	-57.00	-16.16	RMS	
2	253.8760	-63.78	-3.06	-66.84	-57.00	-9.84	RMS	
3 *	322.5520	-64.38	-0.55	-64.93	-57.00	-7.93	RMS	
4	399.9580	-67.88	-0.09	-67.97	-57.00	-10.97	RMS	
5	465.7240	-68.95	2.36	-66.59	-57.00	-9.59	RMS	
6	786.2120	-78.68	8.28	-70.40	-57.00	-13.40	RMS	

Test Mode:	RX Mode 2462 MHz (11n 40M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	168.3220	-69.84	-3.50	-73.34	-57.00	-16.34	RMS	
2	237.7740	-67.73	-2.57	-70.30	-57.00	-13.30	RMS	
3	322.5520	-68.96	-1.40	-70.36	-57.00	-13.36	RMS	
4 *	399.9580	-67.71	1.12	-66.59	-57.00	-9.59	RMS	
5	465.7240	-68.88	2.14	-66.74	-57.00	-9.74	RMS	
6	628.9750	-78.91	6.19	-72.72	-57.00	-15.72	RMS	

Test Mode:	RX Mode 2412 MHz (11b)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.0920	-68.07	8.36	-59.71	-47.00	-12.71	RMS	
2 *	9648.0510	-64.31	12.93	-51.38	-47.00	-4.38	RMS	

Test Mode:	RX Mode 2412 MHz (11b)
------------	------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.0920	-68.34	8.37	-59.97	-47.00	-12.97	RMS	
2 *	9647.9060	-65.62	12.90	-52.72	-47.00	-5.72	RMS	

Test Mode:	RX Mode 2472 MHz (11b)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	9887.9630	-64.28	13.03	-51.25	-47.00	-4.25	RMS	

Test Mode:	RX Mode 2472 MHz (11b)
------------	------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	9888.0439	-65.66	13.15	-52.51	-47.00	-5.51	RMS	

Test Mode:	RX Mode 2412 MHz (11g)
------------	------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.0920	-66.59	8.36	-58.23	-47.00	-11.23	RMS	
2 *	9647.9230	-63.05	12.93	-50.12	-47.00	-3.12	RMS	

Test Mode:	RX Mode 2412 MHz (11g)
------------	------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	5000.0920	-66.61	8.37	-58.24	-47.00	-11.24	RMS	
2 *	9647.8670	-63.62	12.90	-50.72	-47.00	-3.72	RMS	

Test Mode:	RX Mode 2472 MHz (11g)
------------	------------------------


Vertical



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	dBm	Factor	ment	dBm	dB	Detector	Comment
1 *	9888.0610	-62.71	13.03	-49.68	-47.00	-2.68	RMS	

Test Mode:	RX Mode 2472 MHz (11g)
------------	------------------------


Horizontal



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	dBm	Factor	ment	dBm	dB	Detector	Comment
1 *	9887.9300	-64.15	13.15	-51.00	-47.00	-4.00	RMS	

Test Mode:	RX Mode 2412 MHz (11n 20M)
------------	----------------------------


Vertical



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	Level	Factor	ment			Detector	Comment
		dBm	dB	dBm	dBm	dB		
1 *	9647.9250	-62.89	12.93	-49.96	-47.00	-2.96	RMS	

Test Mode:	RX Mode 2412 MHz (11n 20M)
------------	----------------------------


Horizontal



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	dBm	Factor	ment	dBm	dB	Detector	Comment
1 *	9647.9250	-64.07	12.90	-51.17	-47.00	-4.17	RMS	

Test Mode:	RX Mode 2472 MHz (11n 20M)
------------	----------------------------


Vertical



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	dBm	Factor	ment	dBm	dB	Detector	Comment
1 *	9888.0670	-62.67	13.03	-49.64	-47.00	-2.64	RMS	

Test Mode:	RX Mode 2472 MHz (11n 20M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	9887.8930	-64.23	13.15	-51.08	-47.00	-4.08	RMS	

Test Mode: RX Mode 2422 MHz (11n 40M)


Vertical



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	Level	Factor	ment			Detector	Comment
		dBm	dB	dBm	dBm	dB		
1 *	9687.9730	-63.17	12.94	-50.23	-47.00	-3.23	RMS	

Test Mode:	RX Mode 2422 MHz (11n 40M)
------------	----------------------------


Horizontal



No.	Freq.	Reading	Correct	Measure	Limit	Margin		
	MHz	dBm	Factor	ment	dBm	dB	Detector	Comment
1 *	9687.9000	-65.10	12.95	-52.15	-47.00	-5.15	RMS	

Test Mode:	RX Mode 2462 MHz (11n 40M)
------------	----------------------------


Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	9847.8900	-62.95	13.01	-49.94	-47.00	-2.94	RMS	

Test Mode:	RX Mode 2462 MHz (11n 40M)
------------	----------------------------


Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	9847.9410	-65.07	13.11	-51.96	-47.00	-4.96	RMS	

ATTACHMENT J - RECEIVER BLOCKING

802.11b Mode 2412 MHz



802.11b Mode 2472 MHz

